

Project name:	
Fixture type:	
Date:	

# Ixia™ LED Low Voltage Undercabinet Lightbar



#### **Features**

- CCT Tunable (3000K-6500K)
- Linkable up to 12 ft.
- Polycarbonate lens
- Aluminum finish
- Input 24VDC
- Dimmable with EUDCCT/EUDS1
- Mounting brackets included
- 5/8" H x 3/4" W

# **Specifications**

Lumens         160 lm           Voltage         24 VDC           Color Temp.         3000K           Dimmable         EUD51           Lamp Type         LED	Wattage	3W
Color Temp. 3000K Dimmable EUDS1	Lumens	160 lm
Dimmable EUDS1	Voltage	24 VDC
	Color Temp.	3000K
Lamp Type LED	Dimmable	EUDS1
	Lamp Type	LED

#### **Product Number**

Item	Description	Lamp type	Lumens	ССТ	Watts	Voltage	Dimming	Finish
EUN54W	8"	LED	160 lm	3000K	3W	24 VDC	EUDS1	Aluminum

# **Compatible** Products

Ixia® LED Undercabinet Light



# **Accessories**



#### **LED CCT Controller and Dimmer**

CAT NO.	SPECIFICATIONS	
EUDCCT	For EUN51-EUN53 only	



#### **Linking Cable**

CAT NO.	SPECIFICATIONS	
EUDC51	For EUN51-EUN56	



#### **Dimmer Switch**

CAT NO.	SPECIFICATIONS
FUDS1	For FUN54-FUN56 only



#### PIR Sensor Switch

CAT NO.	SPECIFICATIONS	
EUDPH1	For EUN54-EUN56 only	



## **Movement Sensor Switch**

CAT NO.	SPECIFICATIONS
EUDMS1	For EUN54-EUN56 only



#### Input Connector

CAT NO.	SPECIFICATIONS	ı
EUDPC	For EUN54-EUN56 only	



### 24V LED Driver with 6-Way Distributor

CAT NO.	SPECIFICATIONS	
DRV24V30W	For EUN51-EUN56	



# Dimmer Compatibility Chart Undercabinet

**EUD Series** 

## For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
120V Only			
Legrand	CFL/LED Multi-way Paddle Dimmer	HDCL-453	10% - 100%
Leviton	IllumaTech Single Pole/3-Way Preset Electro-Mechanical Electronic Low Voltage Slide Dimmer	IPE04	10% - 100%
	Decora SureSlide® Single Pole/3-Way with Present ON/OFF Switch	6674	5% - 90%
	Rotary Dim N Glo 600W 3-Way Dimmer	DNG-603PH	10% - 100%
Lutron	DIVA® (Gloss) 450W, Single Pole, Magnetic Low Voltage Dimmer	DVLV-600P	10% - 100%
	DIVA® Series 600W Single Pole Dimmer	DV-600P	10% - 100%
	DIVA® Series 150W Single Pole/3-Way Dimmer	DVCL-153P	5% - 86%
	Maestro® Series 150W Single Pole/3-Way/Multi-Location Dimmer	MACL-153M	5% - 80%
	DIVA® (Gloss) 600W 3-Way Preset Eco-dim Dimmer	DV-603PG	10% – 100%

<sup>\*</sup>NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com