

Knuckle Mount LED Floodlights

Small & Medium LED floodlights are ideal for illuminating building facades, wall washing building exteriors, sign lighting, landscape lighting, and improving building security. Heavy-duty die-cast aluminum construction and high quality components ensure ELCO floodlights will provide years of solid performance in almost any weather condition.




Features

- Die-cast Aluminum Housing.
- Durable dark bronze coat finish.
- Knuckle mount for mounting on junction boxes or pipes.
- Trunnion mount for mounting on buildings, walls or flat surfaces. Trunnion mount available upon request.
- 7H x 6V beam angle.
- Clear optic lens.
- 120/277V AC.
- 5000K, CRI70+, 60Hz.
- Photocell available upon request.


Specifications

Wattage	15W - 60W
Lumens	2000 lm - 8000 lm
Voltage	120/277V
Color Temp.	4000K - 5000K
Lamp Type	LED
CRI	70+
Power Factor	> 0.9
Wet Location	cUL Listed

Small



Medium



Technical Details

Lamp: Array LED, CRI 70+

Optics: Clear optic lens

Construction: Die-cast aluminum housing. Dark bronze powder coated finish. Impact, corrosion, and UV resistant

Electrical: Constant current 120/277V AC Driver with a power factor > 0.9. Ambient operating temperature: -40°F (-40°C) to 113°F (45°C). Standard input wattage: 15W (50W metal halide equivalent)

Listings: cUL listed for wet locations. LM-80 certified. IP65 rated.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years

Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Finish
EFL1550S	LED	2000 lm	5000K	15W	120/277V	Dark Bronze
EFL2740S	LED	3400 lm	4000K	27W	120/277V	Dark Bronze
EFL2750S	LED	3600 lm	5000K	27W	120/277V	Dark Bronze
EFL4550M	LED	6000 lm	5000K	45W	120/277V	Dark Bronze
EFL6050M	LED	8000 lm	5000K	60W	120/277V	Dark Bronze

Product Number Builder

Example: **EFL1550S**

Knuckle Mount LED Floodlights

Wattage

Color Temp.

Size

EFL

15 15W (Small Only)

27 27W (Small Only)

45 45W (Medium Only)

60 60W (Medium Only)

40 4000K (EFL27 Only)

50 5000K

S Small

M Medium