

# Knuckle Mount LED Floodlights

Small & Medium LED floodlights are ideal for illuminating building facades, wall washing building exteriors, sign lighting, landscape lighting, and improving building security. Heavy-duty die-cast aluminum construction and high quality components ensure ELCO floodlights will provide years of solid performance in almost any weather condition.




## Features

- Die-cast Aluminum Housing.
- Durable dark bronze coat finish.
- Knuckle mount for mounting on junction boxes or pipes.
- Trunnion mount for mounting on buildings, walls or flat surfaces. Trunnion mount available upon request.
- 7H x 6V beam angle.
- Clear optic lens.
- 120/277V AC.
- 5000K, CRI70+, 60Hz.
- Photocell available upon request.


## Specifications

<b>Wattage</b>	15W
<b>Lumens</b>	2000 lm
<b>Voltage</b>	120/277V
<b>Color Temp.</b>	5000K
<b>Lamp Type</b>	LED
<b>CRI</b>	70+
<b>Power Factor</b>	> 0.9
<b>Wet Location</b>	cUL Listed

## Small



## Medium



## Technical Details

**Lamp:** Array LED, CRI 70+

**Optics:** Clear optic lens

**Construction:** Die-cast aluminum housing. Dark bronze powder coated finish. Impact, corrosion, and UV resistant

**Electrical:** Constant current 120/277V AC Driver with a power factor > 0.9. Ambient operating temperature: -40°F (-40°C) to 113°F (45°C). Standard input wattage: 15W (50W metal halide equivalent)

**Listings:** cUL listed for wet locations. LM-80 certified. IP65 rated.

**Warranty:** ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years

## Product Number

Item	Lamp type	Lumens	CCT	Watts	Voltage	Finish
EFL1550S	LED	2000 lm	5000K	15W	120/277V	Dark Bronze

# Product Number Builder

Example: **EFL1550S**

Knuckle Mount LED Floodlights

Wattage

Color Temp.

Size

**EFL**

**15** 15W (Small Only)

**27** 27W (Small Only)

**45** 45W (Medium Only)

**60** 60W (Medium Only)

**40** 4000K (EFL27 Only)

**50** 5000K

**S** Small

**M** Medium