

# Koto Focus™ Architectural LED Light Engine

Koto™ Adjustable Beam 18° - 50° Angles. Works with 2", 3", 4", 5" and 6" Architectural Koto Housings and Koto™ Trims



## Features

- Includes white and black snout
- Light engine used with Koto™ Architectural Housings
- See Koto™ Architectural housings for lumen output options
- Driver on housing extends lifespan and allows for more dimming and EM options
- Adjustable Focus: 18° to 50° with a simple twist of the lens
- Works in 2", 3", 4", 5" and 6" ELCO housings with Koto™ twist-&-lock trims
- Excellent color rendering 95+ CRI
- Title 24 JA8 2016 Registered
- Life span of 50,000 hours L70
- Covered by U.S. PATENTS and Patents Pending

## Specifications

<b>Wattage</b>	18.9W
<b>Lumens</b>	1360 MAX. lm
<b>Color Temp.</b>	2700K
<b>Lamp Type</b>	LED
<b>Beam Angle</b>	18° - 50°
<b>CRI</b>	95+
<b>Wet Location</b>	cUL Listed w/Wet Location Trim
<b>Damp Location</b>	cUL Listed

## Options



White Snout



Black Snout

## Technical Details

**Optics:** PC lens diffuses light evenly throughout while reducing glare with LED COB technology.

**Construction:** Diecast aluminum body with heat fins allow for efficient cooling.

**Compatible Housings:** Koto™ Module is compatible with Architectural Housings: 120/277V 0-10V/Triac/ELV or 120V Triac/ELV with optional Emergency Battery Backup.

• E3LK65ICA, E3LK66ICAD, E3LK65RICA, ELK72FICA, ELK73FICAD (10W, 250mA) *ELK21 Delivered Lumens:* 2700K: 890 lm, 3000K: 930 lm, 3500K: 990 lm, 4000K: 1020 lm

• E3LK76ICA, E3LK77ICAD, E4LK98ICA, E4LK99ICAD (15W, 350mA) *ELK21 Delivered Lumens:* 2700K:1140 lm, 3000K:1200 lm, 3500K: 1270 lm, 4000K: 1390 lm

• E3LK53ICA, E3LK54ICAD, E4LK47ICA, E4LK48ICAD (17W, 400mA) *ELK21 Delivered Lumens:* 2700K:1220 lm, 3000K:1290 lm, 3500K: 1360 lm, 4000K: 1400 lm


• E3LK85ICAD, E4LK79ICAD (19W, 450mA) *ELK21 Delivered Lumens:* 2700K:1360 lm, 3000K:1430 lm, 3500K: 1510 lm, 4000K: 1690 lm

**Installation:** Twist-lock design for toolless trim installation, for use with Koto™ trims only. Adjustable Focus: 18° to 50° with a simple twist of the lens. Can be used in 2", 3" & 4" Architectural Koto™ Housings only.

**LED Technology:** Extremely accurate Color Rendering Index (CRI) of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness. No LED pixelation.

**Dimmability:** Based on housing used. See Koto™ Architectural Housings for options.

## Dimensions



## Product Number

Item	Lamp type	Lumens	CCT	Watts	Beam Angle
ELK2127D-FC	LED	1360 MAX. lm	2700K	18.9W	18° - 50°

**Listings:** cUL Listed for Damp Locations. cUL Listed for Wet Location with Wet location trims. RoHS Compliant. California Title 24 JA8-2016-E.

**Warranty:** ELCO Products are built to last with a 5-year Limited Warranty.

## Product Number Builder Example: ELK2127D-FC

Koto™ Focus Architectural LED Light Engine	Lumens	Color Temp.	Beam Angle
<input type="text" value="ELK"/>	<input type="text" value="21"/> Up to 1690 lm (18.9W MAX) <sup>1</sup>	<input type="text" value="27D"/> 2700K <input type="text" value="30D"/> 3000K <input type="text" value="35D"/> 3500K <input type="text" value="40D"/> 4000K	<input type="text" value="-FC"/> 18° - 50°


<sup>1</sup> Lumen output varies based on the architectural Koto housing used

# Compatible Products




For use with Koto™ Architectural LED Light Engine

## 2" Koto™ Architectural Recessed Housings




2" Shallow Maximum Adjustability ICA Housing  
 1000 lm (14.7W) w/ELK19 Series Module  
 1200 lm (14.7W) w/ELK21 Series Module  
 1500 lm (14.7W) w/ELK24 Series Module  
**Shallow New Construction**

CAT NO.	SPECIFICATIONS
E2LK34ICA	120V - Triac/ELV
E2LK35ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>



2" Maximum Adjustability ICA Housing  
 1350 lm (15.7W) w/ELK21 Series Module  
 1650 lm (15.7W) w/ELK24 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E2LK41ICA	120V - Triac/ELV
E2LK42ICAD	120/27V - 0-10V/Triac/ELV <sup>1</sup>



2" Maximum Adjustability ICA Housing  
 1500 lm (18.9W) w/ELK21 Series Module  
 1850 lm (18.9W) w/ELK24 Series Module  
**High Lumen New Construction**

CAT NO.	SPECIFICATIONS
E2LK94ICA	120V - Triac/ELV
E2LK95ICAD	120/27V - 0-10V/Triac/ELV <sup>1</sup>

<sup>1</sup> 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver to 1%

## 2" Pex™ Twist-On Trims



**Round Deep Reflector**  
**ELK2818**  
 Finishes:  
 (W, B, H, BB, BZ)




**Round Adjustable Reflector**  
**ELK2829**  
 Finishes:  
 (W, B, H, BB, BZ)




**Round Adjustable Pinhole**  
**ELK2827**  
 Finishes:  
 (W, B, BB, BZ)




**Round Curved Reflector**  
**ELK2872**  
 Finishes:  
 (W, B\*)




**Square Deep Reflector**  
**ELK2518**  
 Finishes:  
 (W, B, BB)



**Square Adjustable Reflector**  
**ELK2529**  
 Finishes:  
 (W, B, BB)




**Square Reflector**  
**ELK2541**  
 Finishes:  
 (W, B, BB)



**Square Adjustable Pinhole**  
**ELK2527**  
 Finishes:  
 (W, B, BB)



**Round Gimbal**  
**ELK2888**  
 Finishes:  
 (W, B\*, BZ)



**Square Gimbal**  
**ELK2588**  
 Finishes:  
 (W, B\*, BZ)



**Round Adj. Trimless Reflector**  
**ELK215**  
 Finishes:  
 (W, B\*)



**Trimless Spackle Frame**  
**EL2SFR**  
 For use with ELK215

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK2872, ELK2888, ELK2588, & ELK215)

# Compatible Products



For use with **Koto™** Architectural LED Light Engine

## 3" Koto™ Architectural Recessed Housings



3" High Lumen Maximum Adjustability ICA Housing  
1500 lm (18.9W) w/ELK21 Series Module  
1650-1850 lm (18.9W) w/ELK24 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E3LK53ICA	120V - Triac/ELV
E3LK54ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>
E3LK84ICA	120V - Triac/ELV
E3LK85ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>



3" Shallow Maximum Adjustability ICA Housing  
850 lm (14.7W) w/ELK19 Series Module  
1100 lm (14.7W) w/ELK21 Series Module  
1500 lm (14.7W) w/ELK24 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E3LK76ICA	120V - Triac/ELV
E3LK77ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>



3" Standard ICA Housing  
750 lm (10.5W) w/ELK19 Series Module  
950 lm (10.5W) w/ELK21 Series Module  
1350 lm (10.5W) w/ELK24 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E3LK65ICA	120V - Triac/ELV
E3LK65ICA-EM1	Emergency Battery Back-Up
E3LK66ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>
E3LK66ICAD-EM1	Emergency Battery Back-Up



3" Standard ICA Housing  
750 lm (10.5W) w/ELK19 Series Module  
950 lm (10.5W) w/ELK21 Series Module  
1350 lm (10.5W) w/ELK24 Series Module  
**Remodel**

CAT NO.	SPECIFICATIONS
E3LK65RICA	120V - Triac/ELV
E3LK66RICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>



2-Hour Fire Rated 3" ICA Housing  
750 lm (10.5W) w/ELK19 Series Module  
950 lm (10.5W) w/ELK21 Series Module  
1350 lm (10.5W) w/ELK24 Series Module  
**New Construction**


CAT NO.	SPECIFICATIONS
ELK72FICA	120V - Triac/ELV
ELK73FICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>

<sup>1</sup>3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver to 1%

## 3" Pex™ Twist-On Trims



**Round Deep Reflector**  
**ELK3618**  
Finishes:  
(W, BB, BZ, B, C, H)



**Round Adjustable Gimbal**  
**ELK3629**  
Finishes:  
(W, BB, BZ, B, C, H)




**Round Adjustable Pinhole**  
**ELK3627**  
Finishes:  
(B, BB, BZ, B, H)




**Round Adj. Slot Aperture**  
**ELK3620**  
Finishes:  
(W)




**Round Adj. Wall Wash**  
**ELK3622**  
Finishes:  
(W)



**Round Regressed Eyeball**  
**ELK3653**  
Finishes:  
(W, BB, B)



**Round Curved Reflector**  
**ELK3672**  
Finishes:  
(W, B)




**Round Directional Gimbal**  
**ELK3679**  
Finishes:  
(W, BB, B, H)

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK3672)

# Compatible Products


For use with **Koto™** Architectural LED Light Engine

## 3" Pex™ Twist-On Trims




**Round Adjustable Baffle**

**ELK3693**  
Finishes:  
**(W)**




**Square Deep Reflector**

**ELK3318**  
Finishes:  
**(W, BB, BZ, B, C, H)**




**Square Adjustable Reflector**

**ELK3329**  
Finishes:  
**(W, BB, BZ, B, C, H)**




**Square Adj. Wall Wash**

**ELK3322**  
Finishes:  
**(W)**



**Square Adjustable Pinhole**

**ELK3327**  
Finishes:  
**(W, BB, BZ, B, H)**



**Square Reflector**


**ELK3341**  
Finishes:  
**(W, BB, BZ, B)**



**Square Adjustable Baffle**

**ELK3393**  
Finishes:  
**(W)**

## 3" Pex™ Flush Mount Trim Adaptors



**Round Flush Mount Trim Adaptor**

**EL3FMR**

Compatible 3" Pex™ Round trims:  
ELK3618, ELK3629, ELK3627, ELK3693,  
ELK3620, ELK3622 Series



**Square Flush Mount Trim Adaptor**

**EL3FMS**

Compatible 3" Pex™ Square trims:  
ELK3318, ELK3329, ELK3322, ELK3327,  
ELK3341, ELK3393 Series

## 3" Pex™ Trimless



**Round Trimless Reflector**

**ELK308**  
Finishes:  
**(W, B, H)**



**Round Adjustable Trimless Reflector**

**ELK315**  
Finishes:  
**(W, B, H)**



**Round Trimless Spackle Frame**

**EL3SFR**  
For use with ELK315



**Round Knife Edge Wood Ceiling Trim w/Mounting Clips**

**EL3WCR**  
Finishes:  
**(W, B)**




**Square Trimless Reflector**

**ELK370**  
Finishes:  
**(W, B, H)**



**Square Adjustable Trimless Reflector**

**ELK381**  
Finishes:  
**(W, B, H)**



**Square Trimless Spackle Frame**


**EL03SFS**  
For use with ELK370 & ELK381

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK315, ELK370, & ELK381)

# Compatible Products


For use with **Koto™ Architectural LED Light Engine**

## 4" Koto™ Architectural Recessed Housings



4" High Lumen Maximum Adjustability ICA Housing  
 1500 lm (15.7W) w/ELK21 Series Module  
 1650-1850 lm (15.7W) w/ELK24 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E4LK47ICA	120V - Triac/ELV
E4LK48ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>
E4LK78ICA	120V - Triac/ELV
E4LK79ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>



4" Shallow Maximum Adjustability ICA Housing  
 850 lm (14.7W) w/ELK19 Series Module  
 1100 lm (14.7W) w/ELK21 Series Module  
 1500 lm (14.7W) w/ELK24 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E4LK98ICA	120V - Triac/ELV
E4LK99ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>



4" Standard ICA Housing  
 750 lm (11.8W) w/ELK19 Series Module  
 950 lm (11.8W) w/ELK21 Series Module  
 1350 lm (11.8W) w/ELK24 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E4LK87ICA	120V - Triac/ELV
E4LK87ICA-EM1	Emergency Battery Back-Up
E4LK88ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>
E4LK88ICAD-EM1	Emergency Battery Back-Up




4" Standard ICA Housing  
 750 lm (11.8W) w/ELK19 Series Module  
 950 lm (11.8W) w/ELK21 Series Module  
 1350 lm (11.8W) w/ELK24 Series Module  
**Remodel**

CAT NO.	SPECIFICATIONS
E4LK87RICA	120V - Triac/ELV
E4LK88RICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>




2-Hour Fire Rated 4" ICA Housing  
 750 lm (11.8W) w/ELK19 Series Module  
 950 lm (11.8W) w/ELK21 Series Module  
 1100 lm (11.8W) w/ELK24 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
ELK93FICA	120V - Triac/ELV
ELK94FICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>



4" ICA Housing for 2-Hr Fire Rated Ceilings  
**New Construction**  
 Compatible Trims: ELK4116, ELK4127, ELK4129, ELK4188, ELK4710, ELK4713, ELK4715, ELK4216, ELK4229, ELK4227, ELK4714, & ELK4716

CAT NO.	SPECIFICATIONS
E4JB85ICA	120V - Triac/ELV
E4JB85ICA-EM1	Emergency Battery Back-Up
E4JB86ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>
E4JB86ICAD-EM1	Emergency Battery Back-Up



4" ICA Housing for 2-Hr Fire Rated Ceilings  
**Remodel**  
 Compatible Trims: ELK4116, ELK4127, ELK4129, ELK4188, ELK4710, ELK4713, ELK4715, ELK4216, ELK4229, ELK4227, ELK4714, & ELK4716


CAT NO.	SPECIFICATIONS
E4JB85RICA	120V - Triac/ELV
E4JB85RICA-EM1	Emergency Battery Back-Up
E4JB86RICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>
E4JB86RICAD-EM1	Emergency Battery Back-Up

<sup>1</sup> 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver to 1%

# Compatible Products

For use with Koto™ Architectural LED Light Engine

## 4" Pex™ Twist-On Trims



**Shallow Reflector**  
**ELK4116**  
Finishes:  
(W, H)



**Deep Reflector**  
**ELK4118**  
Finishes:  
(W, BB, BZ, B, C, H)



**Adjustable Reflector**  
**ELK4129**  
Finishes:  
(W, BB, BZ, B, C, H)



**Adjustable Reflector with Clear Glass**  
**ELK4111**  
Finishes:  
(W, BB, BZ, B, C, H)



**Adjustable Reflector with Frosted Lens**  
**ELK4112**  
Finishes:  
(W, BB, BZ, B, C, H)



**Rotatable Slot Aperture**  
**ELK4120**  
Finishes:  
(W)



**Adjustable Wall Wash**  
**ELK4122**  
Finishes:  
(W)



**Adjustable Pinhole**  
**ELK4127**  
Finishes:  
(W, BB, BZ, B, H)




**Adjustable Pinhole with Frosted Glass**  
**ELK4125**  
Finishes:  
(W, BB, BZ, B, H)




**Slot Aperture**  
**ELK4130**  
Finishes:  
(W)




**Adjustable Spot**  
**ELK4188**  
Finishes:  
(W, B, BZ)




**Regressed Eyeball**  
**ELK4153**  
Finishes:  
(W, BB, B)




**Curved Reflector**  
**ELK4172**  
Finishes:  
(W, B)



**Directional Gimbal**  
**ELK4179**  
Finishes:  
(W, BB, B, H)




**Adjustable Baffle**  
**ELK4193**  
Finishes:  
(W, BB, B)




**Shallow Reflector**  
**ELK4216**  
Finishes:  
(W, H)




**Deep Reflector**  
**ELK4218**  
Finishes:  
(W, BB, BZ, B, C, H)




**Adjustable Gimbal**  
**ELK4229**  
Finishes:  
(W, BB, BZ, B, C, H)




**Adjustable Slot Rotatable Aperture**  
**ELK4220**  
Finishes:  
(W)




**Adjustable Wall Wash**  
**ELK4222**  
Finishes:  
(W)




**Adjustable Pinhole**  
**ELK4227**  
Finishes:  
(W, BB, BZ, B, C, H)



**Adjustable Reflector**  
**ELK4282**  
Finishes:  
(W, BZ)




**Adjustable Baffle**  
**ELK4284**  
Finishes:  
(W, B, BZ)




**Adj. Phenolic Baffle**  
**ELK4293**  
Finishes:  
(W, BB, B)

## 4" Pex™ Flush Mount Trim Adaptors



### Round Flush Mount Trim Adaptor

**EL4FMR**  
Compatible 3" Pex™ Round trims:  
ELK4116, ELK4118, ELK4127, ELK4129,  
ELK4710, ELK4713, ELK4715 Series



### Square Flush Mount Trim Adaptor


**EL4FMS**  
Compatible 3" Pex™ Square trims:  
ELK4216, ELK4218, ELK4227,  
ELK4229 Series

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK4188, ELK4172, & ELK4284)

# Compatible Products

For use with **Koto™** Architectural LED Light Engine

## 4" Pex™ Trimless




**Round Trimless Reflector**

**ELK408**  
Finishes:  
(W, B, H, BZ)




**Round Adj. Trimless Reflector**

**ELK415**  
Finishes:  
(W, B, H, BZ)




**Round Trimless Spackle Frame**

**EL4SFR**  
For use with ELK408 & ELK415




**Smooth Reflector**

**ELK430**  
Finishes:  
(W, B, BZ)




**Baffle**

**ELK434**  
Finishes:  
(W, B, BZ)




**Square Trimless Reflector**

**ELK445**  
Finishes:  
(W, B, H)



**Square Trimless Adj. Reflector**

**ELK459**  
Finishes:  
(W, B, H)



**Square Trimless Spackle Frame**

**EL4SFS**  
For use with ELK445 & ELK459


Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK408, ELK415, ELK434, ELK445, ELK459)

## 4" Flexa™ Twist-On Trims




**Round Reflector**

**ELK4721**  
Finishes:  
(WW, BB, BZBZ, BW, CW, HW)




**Round Baffle**

**ELK4723**  
Finishes:  
(WW, BB, BZBZ, BW)




**Square Reflector**

**ELK4741**  
Finishes:  
(WW, BB, BZBZ, BW, HW)  
*\*Not for Remodel Housing*



**Square Baffle**

**ELK4743**  
Finishes:  
(WW, BB, BZBZ, BW)  
*\*Not for Remodel Housing*



**Square Adj. Reflector**


**ELK4759**  
Finishes:  
(WW, BB, B, H)  
*\*Not for Remodel Housing*

## 4" Unique™ Twist-On Trims




**Round Adjustable Reflector**

**ELK4710**  
Finishes:  
(W, B, BZ)



**Round Adjustable Baffle**

**ELK4713**  
Finishes:  
(W, BZ)




**Round Wall Wash**

**ELK4715**  
Finishes:  
(W, BZ)




**Round Adj. Deep Reflector**

**ELK4717**  
Finishes:  
(W, BZ)




**Round Adj. Deep Baffle**

**ELK4719**  
Finishes:  
(W)



**Square Reflector**

**ELK4714**  
Finishes:  
(W, B, BZ)  
*\*Not for Remodel Housing*



**Square Baffle**

**ELK4716**  
Finishes:  
(W, BZ)  
*\*Not for Remodel Housing*

\*Finishes: **W** - All White, **WW** - All White, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring, **BB** - All Black, **BZ** - All Bronze, **CC** - All Chrome, **BZBZ** - All Bronze, **BW** - Black Reflector w/White Ring, **CW** - Chrome Reflector w/White Ring, **CN** - Chrome Reflector w/Nickel Ring, **HW** - Haze Reflector w/White Ring




# Compatible Products




For use with **Koto™** Architectural LED Light Engine

## 6" Koto™ Architectural Recessed Housings



6" High Lumen Maximum Adjustability ICA Housing  
 1250 lm (15.9W) w/ELK21 Series Module  
 1650-1800 lm (18.9W) w/ELK24 Series Module  
**New Construction**



6" Standard ICA Housing  
 1100 lm (14.7W) w/ELK21 Series Module  
 1500 lm (14.7W) w/ELK24 Series Module  
**New Construction**


CAT NO.	SPECIFICATIONS
E6LK43ICA	120V - Triac/ELV
E6LK44ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>
E6LK56ICA	120V - Triac/ELV
E6LK57ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>

CAT NO.	SPECIFICATIONS
E6LK37ICA	120V - Triac/ELV
E6LK37ICA-EM1	Emergency Battery Back-Up
E6LK38ICAD	120/277V - 0-10V/Triac/ELV <sup>1</sup>
E6LK38ICAD-EM1	Emergency Battery Back-Up


## 5" & 6" Pex™ Twist-On Trims




**5" Round Reflector**  
**ELK5421**  
 Finishes:  
 (W)




**5" Round Baffle**  
**ELK5493**  
 Finishes:  
 (W)




**6" Round Reflector**  
**ELK6418**  
 Finishes:  
 (W, BB, BZ, H)




**6" Round Adj. Reflector**  
**ELK6429**  
 Finishes:  
 (W, BB, BZ, H)



**6" Round Adj. Slot Aperture**  
**ELK6420W**  
 Finishes:  
 (W)



**6" Round Adj. Pinhole Reflector**  
**ELK6427**  
 Finishes:  
 (W, B, H)



**6" Square Adj. Reflector**  
**ELK6829**  
 Finishes:  
 (W, BB, H)

## 6" Flexa™ Twist-On Trims




**6" Round Reflector**  
**ELK610**  
 Finishes:  
 (WW, BB, BZBZ, CC, BW, CW, HW)




**6" Round Adjustable Reflector**  
**ELK629**  
 Finishes:  
 (WW, BB, BZBZ, BW, CW, HW)



**6" Round Reflector**  
**ELK6710**  
 Finishes:  
 (W, B, BZ)



**6" Round Baffle**  
**ELK6713**  
 Finishes:  
 (W, BZ)



**6" Round Adjustable Baffle**  
**ELK693**  
 Finishes:  
 (WW, BB, BZBZ, BW)



**6" Round Wall Wash**  
**ELK6715**  
 Finishes:  
 (W, BZ)

## 6" Unique™ Twist-On Trims

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK6710, ELK6713, ELK6715)