

Koto Focus™ Architectural LED Light Engine

Koto™ Adjustable Beam 18° - 50° Angles. Works with 2", 3", 4", 5" and 6" Architectural Koto Housings and Koto™ Trims



Features

- Includes white and black snout
- Light engine used with Koto™ Architectural Housings
- See Koto™ Architectural housings for lumen output options
- Driver on housing extends lifespan and allows for more dimming and EM options
- Adjustable Focus: 18° to 50° with a simple twist of the lens
- Works in 2", 3", 4", 5" and 6" ELCO housings with Koto™ twist-&-lock trims
- Excellent color rendering 95+ CRI
- Title 24 JA8 2016 Registered
- Life span of 50,000 hours L70
- Covered by U.S. PATENTS and Patents Pending

Specifications

Wattage	18.9W
Lumens	1690 MAX. lm
Color Temp.	4000K
Lamp Type	LED
Beam Angle	18° - 50°
CRI	95+
Wet Location	cUL Listed w/Wet Location Trim
Damp Location	cUL Listed

Options



White Snout



Black Snout

Technical Details

Optics: PC lens diffuses light evenly throughout while reducing glare with LED COB technology.

Construction: Diecast aluminum body with heat fins allow for efficient cooling.

Compatible Housings: Koto™ Module is compatible with Architectural Housings: 120/277V 0-10V/Triac/ELV or 120V Triac/ELV with optional Emergency Battery Backup.

• E3LK65ICA, E3LK66ICAD, E3LK65RICA, ELK72FICA, ELK73FICAD (10W, 250mA) *ELK21 Delivered Lumens:* 2700K: 890 lm, 3000K: 930 lm, 3500K: 990 lm, 4000K: 1020 lm

• E3LK76ICA, E3LK77ICAD, E4LK98ICA, E4LK99ICAD (15W, 350mA) *ELK21 Delivered Lumens:* 2700K:1140 lm, 3000K:1200 lm, 3500K: 1270 lm, 4000K: 1390 lm

• E3LK53ICA, E3LK54ICAD, E4LK47ICA, E4LK48ICAD (17W, 400mA) *ELK21 Delivered Lumens:* 2700K:1220 lm, 3000K:1290 lm, 3500K: 1360 lm, 4000K: 1400 lm


• E3LK85ICAD, E4LK79ICAD (19W, 450mA) *ELK21 Delivered Lumens:* 2700K:1360 lm, 3000K:1430 lm, 3500K: 1510 lm, 4000K: 1690 lm

Installation: Twist-lock design for toolless trim installation, for use with Koto™ trims only. Adjustable Focus: 18° to 50° with a simple twist of the lens. Can be used in 2", 3" & 4" Architectural Koto™ Housings only.

LED Technology: Extremely accurate Color Rendering Index (CRI) of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness. No LED pixelation.

Dimmability: Based on housing used. See Koto™ Architectural Housings for options.

Dimensions



Product Number

Item	Lamp type	Lumens	CCT	Watts	Beam Angle
ELK2140D-FC	LED	1690 MAX. lm	4000K	18.9W	18° - 50°

Listings: cUL Listed for Damp Locations. cUL Listed for Wet Location with Wet location trims. RoHS Compliant. California Title 24 JA8-2016-E.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Product Number Builder Example: ELK2127D-FC

Koto™ Focus Architectural LED Light Engine	Lumens	Color Temp.	Beam Angle
<input type="text" value="ELK"/>	<input type="text" value="21"/> Up to 1690 lm (18.9W MAX) ¹	<input type="text" value="27D"/> 2700K <input type="text" value="30D"/> 3000K <input type="text" value="35D"/> 3500K <input type="text" value="40D"/> 4000K	<input type="text" value="-FC"/> 18° - 50°


¹ Lumen output varies based on the architectural Koto housing used

Compatible Products




For use with Koto™ Architectural LED Light Engine

2" Koto™ Architectural Recessed Housings




2" Shallow Maximum Adjustability ICA Housing
 1000 lm (14.7W) w/ELK19 Series Module
 1200 lm (14.7W) w/ELK21 Series Module
 1500 lm (14.7W) w/ELK24 Series Module
Shallow New Construction

CAT NO.	SPECIFICATIONS
E2LK34ICA	120V - Triac/ELV
E2LK35ICAD	120/277V - 0-10V/Triac/ELV ¹



2" Maximum Adjustability ICA Housing
 1350 lm (15.7W) w/ELK21 Series Module
 1650 lm (15.7W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E2LK41ICA	120V - Triac/ELV
E2LK42ICAD	120/27V - 0-10V/Triac/ELV ¹



2" Maximum Adjustability ICA Housing
 1500 lm (18.9W) w/ELK21 Series Module
 1850 lm (18.9W) w/ELK24 Series Module
High Lumen New Construction

CAT NO.	SPECIFICATIONS
E2LK94ICA	120V - Triac/ELV
E2LK95ICAD	120/27V - 0-10V/Triac/ELV ¹

¹ 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver to 1%

2" Pex™ Twist-On Trims



Round Deep Reflector

ELK2818
 Finishes:
 (W, B, H, BB, BZ)



Round Adjustable Reflector

ELK2829
 Finishes:
 (W, B, H, BB, BZ)




Round Adjustable Pinhole

ELK2827
 Finishes:
 (W, B, BB, BZ)




Round Curved Reflector

ELK2872
 Finishes:
 (W, B*)




Square Deep Reflector

ELK2518
 Finishes:
 (W, B, BB)




Square Adjustable Reflector

ELK2529
 Finishes:
 (W, B, BB)



Square Reflector

ELK2541
 Finishes:
 (W, B, BB)




Square Adjustable Pinhole

ELK2527
 Finishes:
 (W, B, BB)



Round Gimbal
 ELK2888
 Finishes:
 (W, B*, BZ)



Square Gimbal
 ELK2588
 Finishes:
 (W, B*, BZ)



Round Adj. Trimless Reflector
 ELK215
 Finishes:
 (W, B*)



Trimless Spackle Frame
 EL2SFR
 For use with ELK215


Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK2872, ELK2888, ELK2588, & ELK215)

Compatible Products




For use with **Koto™** Architectural LED Light Engine

3" Koto™ Architectural Recessed Housings



3" High Lumen Maximum Adjustability ICA Housing
1500 lm (18.9W) w/ELK21 Series Module
1650-1850 lm (18.9W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E3LK53ICA	120V - Triac/ELV
E3LK54ICAD	120/277V - 0-10V/Triac/ELV ¹
E3LK84ICA	120V - Triac/ELV
E3LK85ICAD	120/277V - 0-10V/Triac/ELV ¹



3" Shallow Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
1500 lm (14.7W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E3LK76ICA	120V - Triac/ELV
E3LK77ICAD	120/277V - 0-10V/Triac/ELV ¹



3" Standard ICA Housing
750 lm (10.5W) w/ELK19 Series Module
950 lm (10.5W) w/ELK21 Series Module
1350 lm (10.5W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E3LK65ICA	120V - Triac/ELV
E3LK65ICA-EM1	Emergency Battery Back-Up
E3LK66ICAD	120/277V - 0-10V/Triac/ELV ¹
E3LK66ICAD-EM1	Emergency Battery Back-Up



3" Standard ICA Housing
750 lm (10.5W) w/ELK19 Series Module
950 lm (10.5W) w/ELK21 Series Module
1350 lm (10.5W) w/ELK24 Series Module
Remodel

CAT NO.	SPECIFICATIONS
E3LK65RICA	120V - Triac/ELV
E3LK66RICAD	120/277V - 0-10V/Triac/ELV ¹



2-Hour Fire Rated 3" ICA Housing
750 lm (10.5W) w/ELK19 Series Module
950 lm (10.5W) w/ELK21 Series Module
1350 lm (10.5W) w/ELK24 Series Module
New Construction


CAT NO.	SPECIFICATIONS
ELK72FICA	120V - Triac/ELV
ELK73FICAD	120/277V - 0-10V/Triac/ELV ¹

¹3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver to 1%

3" Pex™ Twist-On Trims



Round Deep Reflector
ELK3618
Finishes:
(W, BB, BZ, B, C, H)



Round Adjustable Gimbal
ELK3629
Finishes:
(W, BB, BZ, B, C, H)




Round Adjustable Pinhole
ELK3627
Finishes:
(B, BB, BZ, B, H)




Round Adj. Slot Aperture
ELK3620
Finishes:
(W)




Round Adj. Wall Wash
ELK3622
Finishes:
(W)



Round Regressed Eyeball
ELK3653
Finishes:
(W, BB, B)



Round Curved Reflector
ELK3672
Finishes:
(W, B)




Round Directional Gimbal
ELK3679
Finishes:
(W, BB, B, H)

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK3672)

Compatible Products


For use with **Koto™** Architectural LED Light Engine

3" Pex™ Twist-On Trims




Round Adjustable Baffle

ELK3693
Finishes:
(W)




Square Deep Reflector

ELK3318
Finishes:
(W, BB, BZ, B, C, H)




Square Adjustable Reflector

ELK3329
Finishes:
(W, BB, BZ, B, C, H)




Square Adj. Wall Wash

ELK3322
Finishes:
(W)




Square Adjustable Pinhole

ELK3327
Finishes:
(W, BB, BZ, B, H)



Square Reflector


ELK3341
Finishes:
(W, BB, BZ, B)



Square Adjustable Baffle

ELK3393
Finishes:
(W)


3" Pex™ Flush Mount Trim Adaptors



Round Flush Mount Trim Adaptor

EL3FMR

Compatible 3" Pex™ Round trims:
ELK3618, ELK3629, ELK3627, ELK3693,
ELK3620, ELK3622 Series




Square Flush Mount Trim Adaptor

EL3FMS

Compatible 3" Pex™ Square trims:
ELK3318, ELK3329, ELK3322, ELK3327,
ELK3341, ELK3393 Series

3" Pex™ Trimless




Round Trimless Reflector

ELK308
Finishes:
(W, B, H)



Round Adjustable Trimless Reflector

ELK315
Finishes:
(W, B, H)



Round Trimless Spackle Frame

EL3SFR
For use with ELK315



Round Knife Edge Wood Ceiling Trim w/Mounting Clips

EL3WCR
Finishes:
(W, B)




Square Trimless Reflector

ELK370
Finishes:
(W, B, H)



Square Adjustable Trimless Reflector

ELK381
Finishes:
(W, B, H)



Square Trimless Spackle Frame


EL03SFS
For use with ELK370 & ELK381

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK315, ELK370, & ELK381)

Compatible Products


For use with **Koto™ Architectural LED Light Engine**

4" Koto™ Architectural Recessed Housings




4" High Lumen Maximum Adjustability ICA Housing
 1500 lm (15.7W) w/ELK21 Series Module
 1650-1850 lm (15.7W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK47ICA	120V - Triac/ELV
E4LK48ICAD	120/277V - 0-10V/Triac/ELV ¹
E4LK78ICA	120V - Triac/ELV
E4LK79ICAD	120/277V - 0-10V/Triac/ELV ¹



4" Shallow Maximum Adjustability ICA Housing
 850 lm (14.7W) w/ELK19 Series Module
 1100 lm (14.7W) w/ELK21 Series Module
 1500 lm (14.7W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK98ICA	120V - Triac/ELV
E4LK99ICAD	120/277V - 0-10V/Triac/ELV ¹



4" Standard ICA Housing
 750 lm (11.8W) w/ELK19 Series Module
 950 lm (11.8W) w/ELK21 Series Module
 1350 lm (11.8W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK87ICA	120V - Triac/ELV
E4LK87ICA-EM1	Emergency Battery Back-Up
E4LK88ICAD	120/277V - 0-10V/Triac/ELV ¹
E4LK88ICAD-EM1	Emergency Battery Back-Up




4" Standard ICA Housing
 750 lm (11.8W) w/ELK19 Series Module
 950 lm (11.8W) w/ELK21 Series Module
 1350 lm (11.8W) w/ELK24 Series Module
Remodel

CAT NO.	SPECIFICATIONS
E4LK87RICA	120V - Triac/ELV
E4LK88RICAD	120/277V - 0-10V/Triac/ELV ¹




2-Hour Fire Rated 4" ICA Housing
 750 lm (11.8W) w/ELK19 Series Module
 950 lm (11.8W) w/ELK21 Series Module
 1100 lm (11.8W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
ELK93FICA	120V - Triac/ELV
ELK94FICAD	120/277V - 0-10V/Triac/ELV ¹



4" ICA Housing for 2-Hr Fire Rated Ceilings
New Construction
 Compatible Trims: ELK4116, ELK4127, ELK4129, ELK4188, ELK4710, ELK4713, ELK4715, ELK4216, ELK4229, ELK4227, ELK4714, & ELK4716

CAT NO.	SPECIFICATIONS
E4JB85ICA	120V - Triac/ELV
E4JB85ICA-EM1	Emergency Battery Back-Up
E4JB86ICAD	120/277V - 0-10V/Triac/ELV ¹
E4JB86ICAD-EM1	Emergency Battery Back-Up



4" ICA Housing for 2-Hr Fire Rated Ceilings
Remodel
 Compatible Trims: ELK4116, ELK4127, ELK4129, ELK4188, ELK4710, ELK4713, ELK4715, ELK4216, ELK4229, ELK4227, ELK4714, & ELK4716


CAT NO.	SPECIFICATIONS
E4JB85RICA	120V - Triac/ELV
E4JB85RICA-EM1	Emergency Battery Back-Up
E4JB86RICAD	120/277V - 0-10V/Triac/ELV ¹
E4JB86RICAD-EM1	Emergency Battery Back-Up

¹ 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver to 1%

Compatible Products

For use with Koto™ Architectural LED Light Engine

4" Pex™ Twist-On Trims



Shallow Reflector
ELK4116
Finishes:
(W, H)



Deep Reflector
ELK4118
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Reflector
ELK4129
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Reflector with Clear Glass
ELK4111
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Reflector with Frosted Lens
ELK4112
Finishes:
(W, BB, BZ, B, C, H)



Rotatable Slot Aperture
ELK4120
Finishes:
(W)



Adjustable Wall Wash
ELK4122
Finishes:
(W)



Adjustable Pinhole
ELK4127
Finishes:
(W, BB, BZ, B, H)




Adjustable Pinhole with Frosted Glass
ELK4125
Finishes:
(W, BB, BZ, B, H)




Slot Aperture
ELK4130
Finishes:
(W)




Adjustable Spot
ELK4188
Finishes:
(W, B, BZ)




Regressed Eyeball
ELK4153
Finishes:
(W, BB, B)




Curved Reflector
ELK4172
Finishes:
(W, B)



Directional Gimbal
ELK4179
Finishes:
(W, BB, B, H)




Adjustable Baffle
ELK4193
Finishes:
(W, BB, B)




Shallow Reflector
ELK4216
Finishes:
(W, H)




Deep Reflector
ELK4218
Finishes:
(W, BB, BZ, B, C, H)




Adjustable Gimbal
ELK4229
Finishes:
(W, BB, BZ, B, C, H)




Adjustable Slot Rotatable Aperture
ELK4220
Finishes:
(W)




Adjustable Wall Wash
ELK4222
Finishes:
(W)




Adjustable Pinhole
ELK4227
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Reflector
ELK4282
Finishes:
(W, BZ)




Adjustable Baffle
ELK4284
Finishes:
(W, B, BZ)




Adj. Phenolic Baffle
ELK4293
Finishes:
(W, BB, B)

4" Pex™ Flush Mount Trim Adaptors



Round Flush Mount Trim Adaptor

EL4FMR
Compatible 3" Pex™ Round trims:
ELK4116, ELK4118, ELK4127, ELK4129,
ELK4710, ELK4713, ELK4715 Series



Square Flush Mount Trim Adaptor


EL4FMS
Compatible 3" Pex™ Square trims:
ELK4216, ELK4218, ELK4227,
ELK4229 Series

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK4188, ELK4172, & ELK4284)

Compatible Products

For use with **Koto™** Architectural LED Light Engine

4" Pex™ Trimless




Round Trimless Reflector

ELK408
Finishes:
(W, B, H, BZ)




Round Adj. Trimless Reflector

ELK415
Finishes:
(W, B, H, BZ)




Round Trimless Spackle Frame

EL4SFR
For use with ELK408 & ELK415




Smooth Reflector

ELK430
Finishes:
(W, B, BZ)




Baffle

ELK434
Finishes:
(W, B, BZ)




Square Trimless Reflector

ELK445
Finishes:
(W, B, H)



Square Trimless Adj. Reflector

ELK459
Finishes:
(W, B, H)



Square Trimless Spackle Frame

EL4SFS
For use with ELK445 & ELK459


Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK408, ELK415, ELK434, ELK445, ELK459)

4" Flexa™ Twist-On Trims




Round Reflector

ELK4721
Finishes:
(WW, BB, BZBZ, BW, CW, HW)




Round Baffle

ELK4723
Finishes:
(WW, BB, BZBZ, BW)




Square Reflector

ELK4741
Finishes:
(WW, BB, BZBZ, BW, HW)
**Not for Remodel Housing*



Square Baffle

ELK4743
Finishes:
(WW, BB, BZBZ, BW)
**Not for Remodel Housing*



Square Adj. Reflector


ELK4759
Finishes:
(WW, BB, B, H)
**Not for Remodel Housing*

4" Unique™ Twist-On Trims




Round Adjustable Reflector

ELK4710
Finishes:
(W, B, BZ)



Round Adjustable Baffle

ELK4713
Finishes:
(W, BZ)




Round Wall Wash

ELK4715
Finishes:
(W, BZ)




Round Adj. Deep Reflector

ELK4717
Finishes:
(W, BZ)




Round Adj. Deep Baffle

ELK4719
Finishes:
(W)



Square Reflector

ELK4714
Finishes:
(W, B, BZ)
**Not for Remodel Housing*



Square Baffle


ELK4716
Finishes:
(W, BZ)
**Not for Remodel Housing*

*Finishes: **W** - All White, **WW** - All White, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring, **BB** - All Black, **BZ** - All Bronze, **CC** - All Chrome, **BZBZ** - All Bronze, **BW** - Black Reflector w/White Ring, **CW** - Chrome Reflector w/White Ring, **CN** - Chrome Reflector w/Nickel Ring, **HW** - Haze Reflector w/White Ring


Compatible Products

For use with **Koto™** Architectural LED Light Engine

6" Koto™ Architectural Recessed Housings



6" High Lumen Maximum Adjustability ICA Housing
 1250 lm (15.9W) w/ELK21 Series Module
 1650-1800 lm (18.9W) w/ELK24 Series Module
New Construction




6" Standard ICA Housing
 1100 lm (14.7W) w/ELK21 Series Module
 1500 lm (14.7W) w/ELK24 Series Module
New Construction


CAT NO.	SPECIFICATIONS
E6LK43ICA	120V - Triac/ELV
E6LK44ICAD	120/277V - 0-10V/Triac/ELV ¹
E6LK56ICA	120V - Triac/ELV
E6LK57ICAD	120/277V - 0-10V/Triac/ELV ¹

CAT NO.	SPECIFICATIONS
E6LK37ICA	120V - Triac/ELV
E6LK37ICA-EM1	Emergency Battery Back-Up
E6LK38ICAD	120/277V - 0-10V/Triac/ELV ¹
E6LK38ICAD-EM1	Emergency Battery Back-Up


5" & 6" Pex™ Twist-On Trims




5" Round Reflector
ELK5421
 Finishes:
 (W)




5" Round Baffle
ELK5493
 Finishes:
 (W)




6" Round Reflector
ELK6418
 Finishes:
 (W, BB, BZ, H)




6" Round Adj. Reflector
ELK6429
 Finishes:
 (W, BB, BZ, H)



6" Round Adj. Slot Aperture
ELK6420W
 Finishes:
 (W)



6" Round Adj. Pinhole Reflector
ELK6427
 Finishes:
 (W, B, H)




6" Square Adj. Reflector
ELK6829
 Finishes:
 (W, BB, H)

6" Flexa™ Twist-On Trims




6" Round Reflector
ELK610
 Finishes:
 (WW, BB, BZBZ, CC, BW, CW, HW)




6" Round Adjustable Reflector
ELK629
 Finishes:
 (WW, BB, BZBZ, BW, CW, HW)



6" Round Reflector
ELK6710
 Finishes:
 (W, B, BZ)



6" Round Baffle
ELK6713
 Finishes:
 (W, BZ)



6" Round Adjustable Baffle
ELK693
 Finishes:
 (WW, BB, BZBZ, BW)



6" Round Wall Wash
ELK6715
 Finishes:
 (W, BZ)

6" Unique™ Twist-On Trims

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK6710, ELK6713, ELK6715)