

# Koto™ LED Module with 5-CCT Switch

Works with 2", 3", 4" & 6" Recessed Housings and Koto™ Trims




## Features

- 5-CCT Switch allows to choose between 2700K, 3000K, 3500K, 4000K or 5000K
  - Integrated 120V dimmable driver Triac/ELV
  - Excellent color rendering 90+ CRI
  - Works in 2", 3", 4" & 6" ELCO Housings with Koto™ twist-on trims
  - Energy Star Certified. Title 24 JA8-2019 Compliant
  - Standard 38° Lens installed, 25° and 60° lens included with each module - Optional Lens: 18° (EP731C), 90° (EP739C)
  - Optional: Louver (L45), Linear Lens (L46), Spread Lens (L47), Clear Lens (L48), Frosted Lens (L49), White Koto Snoot (L50W), Black Koto Snoot (L50B), Color Shifter (L51), Blue Lens (L52), Pink Lens (L53), Single Asymmetric Lens (L54), Double Asymmetric Lens (L55)
  - Covered by U.S. PATENTS and Patents Pending
- Please note this will not replace static color temperature Koto modules.

## Specifications

<b>Wattage</b>	10.5W
<b>Lumens</b>	825 lm
<b>Voltage</b>	120V
<b>Color Temp.</b>	2700K, 3000K, 3500K, 4000K, 5000K
<b>Dimmable</b>	Triac/ELV
<b>Lamp Type</b>	LED
<b>Beam Angle</b>	18°
<b>CRI</b>	95
<b>Wet Location</b>	cUL Listed w/Wet Location Trim
<b>Damp Location</b>	cUL Listed

## Dimensions



## Technical Details

**Optics:** Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

**Construction:** Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allow for efficient cooling.

**Installation:** Twist-on design for toolless trim installation, for use with Koto™ trims only. Can be use in 2", 3", 4" & 6" housings with quick connect base.

**Electrical:** Module connects to 120 power supply. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

**Delivered Lumens:** Up to 1000 lm/5-CCT Switch

**LED Technology:** Extremely accurate Color Rendering Index of 90+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixilation.

**Dimmability:** Works with 120V Triac and ELV type dimmers. Dims down to 5%. For full list of dimmers, refer to the Dimmer Compatibility List. Industry leading dimming that dims smoothly with no hot spots or flickering.

**Listings:** cUL Listed for Damp Locations. cUL Listed for Wet Location with Wet location trims. RoHS Compliant. Energy Star Certified. Title 24 JA8-2019 Compliant

## Product Number

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle
ELK08CT5-S	LED	825 lm	2700K, 3000K, 3500K, 4000K, 5000K	10.5W	120V	Triac/ELV	18°

**Warranty:** ELCO Products are built to last with a 5-year Limited Warranty.

## Product Number Builder Example: ELK08CT5

Koto™ LED Module	Lumens	Color Temperature	Beam Angle
<b>ELK</b>			
	<b>08</b> 825 lm (10.5W) <b>10</b> 1000 lm (12.5W)	<b>CT5</b> 2700K - 5000K	38° <sup>1</sup> <b>-S</b> 18° <b>-N</b> 25° <b>-W</b> 60° <b>-E</b> 90° <sup>2</sup>

<sup>1</sup> 38° lens installed. Includes 25° and 60° lens with module.


<sup>2</sup> 90° Frosted Reflector

# Compatible Products



For use with **Koto™ LED Module**


## 2" Koto™ Dedicated LED ICA Housings



2" ICA Maximum Adjustability Housing  
**New Construction**


CAT NO.	SPECIFICATIONS
EL276ICA	Maximum Adjustability

## 2" Pex™ Twist-On Trims



**Round Deep Reflector**

**ELK2818**  
Finishes:  
(W, B, H, BB, BZ)



**Round Adjustable Reflector**

**ELK2829**  
Finishes:  
(W, B, H, BB, BZ)




**Round Adjustable Pinhole**

**ELK2827**  
Finishes:  
(W, B, BB, BZ)




**Round Curved Reflector**

**ELK2872**  
Finishes:  
(W, B\*)




**Square Deep Reflector**

**ELK2518**  
Finishes:  
(W, B, BB)




**Square Adjustable Reflector**

**ELK2529**  
Finishes:  
(W, B, BB)




**Square Reflector**

**ELK2541**  
Finishes:  
(W, B, BB)




**Square Adjustable Pinhole**

**ELK2527**  
Finishes:  
(W, B, BB)



**Round Gimbal**

**ELK2888**  
Finishes:  
(W, B\*, BZ)




**Square Gimbal**

**ELK2588**  
Finishes:  
(W, B\*, BZ)



**Round Adj. Trimless Reflector**

**ELK215**  
Finishes:  
(W, B\*)



**Trimless Spackle Frame**

**EL2SFR**  
For use with ELK215

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK2872, ELK2888, ELK2588, & ELK215)

# Compatible Products




For use with **Koto™ LED Module**

## 3" Koto™ Dedicated LED ICA Housings




2-Hour Fire Rated 3" ICA Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL39FICA	7 1/2" Height - Sound Rated



3" ICA Maximum Adjustability Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL386ICA	Maximum Adjustability



3" ICA Housing  
**New Construction**


CAT NO.	SPECIFICATIONS
EL390ICA	
EL390ICA-EM5	Emergency Battery Back-up (90 minutes)




3" ICA Housing  
**Remodel**

CAT NO.	SPECIFICATIONS
EL390ICA	


## 3" Pex™ Twist-On Trims



**Round Deep Reflector**  
**ELK3618**  
Finishes:  
(W, BB, BZ, B, C, H)



**Round Adjustable Gimbal**  
**ELK3629**  
Finishes:  
(W, BB, BZ, B, C, H)




**Round Adjustable Pinhole**  
**ELK3627**  
Finishes:  
(B, BB, BZ, B, H)



**Round Adj. Slot Aperture**  
**ELK3620**  
Finishes:  
(W)



**Round Adj. Wall Wash**  
**ELK3622**  
Finishes:  
(W)




**Round Regressed Eyeball**  
**ELK3653**  
Finishes:  
(W, BB, B)




**Round Curved Reflector**  
**ELK3672**  
Finishes:  
(W, B)




**Round Directional Gimbal**  
**ELK3679**  
Finishes:  
(W, BB, B, H)




**Round Adjustable Baffle**  
**ELK3693**  
Finishes:  
(W)



**Square Deep Reflector**  
**ELK3318**  
Finishes:  
(W, BB, BZ, B, C, H)



**Square Adjustable Reflector**  
**ELK3329**  
Finishes:  
(W, BB, BZ, B, C, H)




**Square Adj. Wall Wash**  
**ELK3322**  
Finishes:  
(W)

\*Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring


# Compatible Products

For use with **Koto™ LED Module**


## 3" Pex™ Twist-On Trims



**Square Adjustable Pinhole**  
**ELK3327**  
 Finishes:  
 (W, BB, BZ, B, H)




**Square Reflector**  
**ELK3341**  
 Finishes:  
 (W, BB, BZ, B)




**Square Adjustable Baffle**  
**ELK3393**  
 Finishes:  
 (W)

## 3" Pex™ Flush Mount Trim Adaptors



**Round Flush Mount Trim Adaptor**  
**EL3FMR**  
 Compatible 3" Pex™ Round trims:  
 ELK3618, ELK3629, ELK3627, ELK3693,  
 ELK3620, ELK3622 Series



**Square Flush Mount Trim Adaptor**  
**EL3FMS**  
 Compatible 3" Pex™ Square trims:  
 ELK3318, ELK3329, ELK3322, ELK3327,  
 ELK3341, ELK3393 Series

## 3" Pex™ Trimless



**Round Trimless Reflector**  
**ELK308**  
 Finishes:  
 (W, B, H)



**Round Adjustable Trimless Reflector**  
**ELK315**  
 Finishes:  
 (W, B, H)



**Round Trimless Spackle Frame**  
**EL3SFR**  
 For use with ELK315




**Round Knife Edge Wood Ceiling Trim w/Mounting Clips**  
**EL3WCR**  
 Finishes:  
 (W, B)



**Square Trimless Reflector**  
**ELK370**  
 Finishes:  
 (W, B, H)



**Square Adjustable Trimless Reflector**  
**ELK381**  
 Finishes:  
 (W, B, H)



**Square Trimless Spackle Frame**  
**EL03SFS**  
 For use with ELK370 & ELK381


Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK315, ELK370, & ELK381)

# Compatible Products




For use with **Koto™ LED Module**

## 4" Koto™ Dedicated LED ICA Housings




4" ICA Maximum Adjustability Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL485ICA	Maximum Adjustability



4" ICA Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL490ICA	14W, 120/277V
EL490ICA-EM5	Emergency Battery Back-up (90 minutes)




4" R-60 Spray Foam Insulation Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL490AJICA	Maximum Adjustability, For use in R60 or Chicago plenum applications



4" ICA Housing  
**Remodel**


CAT NO.	SPECIFICATIONS
EL490RICA	14W, 120V



2-Hour Fire Rated 4" ICA Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL48FICA	7 1/2" Height, Sound Rated

## 4" Pex™ Twist-On Trims



**Shallow Reflector**  
**ELK4116**  
Finishes:  
(W, H)



**Deep Reflector**  
**ELK4118**  
Finishes:  
(W, BB, BZ, B, C, H)



**Adjustable Reflector**  
**ELK4129**  
Finishes:  
(W, BB, BZ, B, C, H)



**Adjustable Reflector with Clear Glass**  
**ELK4111**  
Finishes:  
(W, BB, BZ, B, C, H)



**Adjustable Reflector with Frosted Lens**  
**ELK4112**  
Finishes:  
(W, BB, BZ, B, C, H)



**Rotatable Slot Aperture**  
**ELK4120**  
Finishes:  
(W)



**Adjustable Wall Wash**  
**ELK4122**  
Finishes:  
(W)




**Adjustable Pinhole**  
**ELK4127**  
Finishes:  
(W, BB, BZ, B, H)



**Adjustable Pinhole with Frosted Glass**  
**ELK4125**  
Finishes:  
(W, BB, BZ, B, H)



**Slot Aperture**  
**ELK4130**  
Finishes:  
(W)



**Adjustable Spot**  
**ELK4188**  
Finishes:  
(W, B, BZ)



**Regressed Eyeball**  
**ELK4153**  
Finishes:  
(W, BB, B)



**Curved Reflector**  
**ELK4172**  
Finishes:  
(W, B)



**Directional Gimbal**  
**ELK4179**  
Finishes:  
(W, BB, B, H)




**Adjustable Baffle**  
**ELK4193**  
Finishes:  
(W, BB, B)

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK4188, ELK4172, & ELK4284)

# Compatible Products

For use with **Koto™ LED Module**

## 4" Pex™ Twist-On Trims




**Shallow Reflector**

**ELK4216**  
Finishes:  
(W, H)




**Deep Reflector**

**ELK4218**  
Finishes:  
(W, BB, BZ, B, C, H)




**Adjustable Gimbal**

**ELK4229**  
Finishes:  
(W, BB, BZ, B, C, H)




**Adjustable Slot Rotatable Aperture**

**ELK4220**  
Finishes:  
(W)




**Adjustable Wall Wash**

**ELK4222**  
Finishes:  
(W)




**Adjustable Pinhole**

**ELK4227**  
Finishes:  
(W, BB, BZ, B, C, H)




**Adjustable Reflector**

**ELK4282**  
Finishes:  
(W, BZ)



**Adjustable Baffle**


**ELK4284**  
Finishes:  
(W, B, BZ)



**Adj. Phenolic Baffle**


**ELK4293**  
Finishes:  
(W, BB, B)

## 4" Pex™ Flush Mount Trim Adaptors



**Round Flush Mount Trim Adaptor**

**EL4FMR**  
Compatible 3" Pex™ Round trims:  
ELK4116, ELK4118, ELK4127, ELK4129,  
ELK4710, ELK4713, ELK4715 Series



**Square Flush Mount Trim Adaptor**

**EL4FMS**  
Compatible 3" Pex™ Square trims:  
ELK4216, ELK4218, ELK4227,  
ELK4229 Series

## 4" Pex™ Trimless




**Round Trimless Reflector**

**ELK408**  
Finishes:  
(W, B, H, BZ)




**Round Adj. Trimless Reflector**

**ELK415**  
Finishes:  
(W, B, H, BZ)



**Round Trimless Spackle Frame**

**EL4SFR**  
For use with ELK408 & ELK415




**Smooth Reflector**

**ELK430**  
Finishes:  
(W, B, BZ)




**Baffle**

**ELK434**  
Finishes:  
(W, B, BZ)




**Square Trimless Reflector**

**ELK445**  
Finishes:  
(W, B, H)



**Square Trimless Adj. Reflector**

**ELK459**  
Finishes:  
(W, B, H)



**Square Trimless Spackle Frame**

**EL4SFS**  
For use with ELK445 & ELK459

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK408, ELK415, ELK434, ELK445, ELK459)

# Compatible Products




For use with **Koto™ LED Module**

## 4" Flexa™ Twist-On Trims




**Round Reflector**

**ELK4721**  
 Finishes:  
 (WW, BB, BZBZ,  
 BW, CW, HW)




**Round Baffle**

**ELK4723**  
 Finishes:  
 (WW, BB, BZBZ, BW)




**Square Reflector**

**ELK4741**  
 Finishes:  
 (WW, BB, BZBZ,  
 BW, HW)  
*\*Not for Remodel Housing*



**Square Baffle**

**ELK4743**  
 Finishes:  
 (WW, BB, BZBZ, BW)  
*\*Not for Remodel Housing*



**Square Adj. Reflector**


**ELK4759**  
 Finishes:  
 (WW, BB, B, H)  
*\*Not for Remodel Housing*

## 4" Unique™ Twist-On Trims




**Round Adjustable Reflector**

**ELK4710**  
 Finishes:  
 (W, B, BZ)




**Round Adjustable Baffle**

**ELK4713**  
 Finishes:  
 (W, BZ)




**Round Wall Wash**

**ELK4715**  
 Finishes:  
 (W, BZ)




**Round Adj. Deep Reflector**

**ELK4717**  
 Finishes:  
 (W, BZ)




**Round Adj. Deep Baffle**

**ELK4719**  
 Finishes:  
 (W)



**Square Reflector**

**ELK4714**  
 Finishes:  
 (W, B, BZ)  
*\*Not for Remodel Housing*



**Square Baffle**

**ELK4716**  
 Finishes:  
 (W, BZ)  
*\*Not for Remodel Housing*

\*Finishes: **W** - All White, **WW** - All White, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring, **BB** - All Black, **BZ** - All Bronze, **CC** - All Chrome, **BZBZ** - All Bronze, **BW** - Black Reflector w/White Ring, **CW** - Chrome Reflector w/White Ring, **CN** - Chrome Reflector w/Nickel Ring, **HW** - Haze Reflector w/White Ring



# Compatible Products


For use with **Koto™ LED Module**

## 6" Koto™ Dedicated LED ICA Housings




2-Hour Fire Rated 6" ICA Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL76FICA	7 3/4" Height




6" Standard ICA Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL770ICA	7 1/2" Height




6" Standard ICA Housing  
**Remodel**

CAT NO.	SPECIFICATIONS
EL770RICA	7 1/2" Height




2-Hour Shallow Fire Rated 6" ICA Housing  
**New Construction**

CAT NO.	SPECIFICATIONS
EL75FICAS	6 3/16" Height



6" Shallow ICA Housing  
**New Construction**


CAT NO.	SPECIFICATIONS
EL760ICA	5 1/2" Height




6" Shallow ICA Housing  
**Remodel**

CAT NO.	SPECIFICATIONS
EL760RICA	5 1/2" Height


## 5" & 6" Pex™ Twist-On Trims




**5" Round Reflector**  
ELK5421  
Finishes:  
**(W)**



**5" Round Baffle**  
ELK5493  
Finishes:  
**(W)**



**6" Round Reflector**  
ELK6418  
Finishes:  
**(W, BB, BZ, H)**




**6" Round Adj. Reflector**  
ELK6429  
Finishes:  
**(W, BB, BZ, H)**



**6" Round Adj. Slot Aperture**  
ELK6420W  
Finishes:  
**(W)**



**6" Round Adj. Pinhole Reflector**  
ELK6427  
Finishes:  
**(W, B, H)**



**6" Square Adj. Reflector**  
ELK6829  
Finishes:  
**(W, BB, H)**

\*Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring

# Compatible Products

For use with **Koto™ LED Module**

## 6" Flexa™ Twist-On Trims

---



**6" Round Reflector**

**ELK610**

Finishes:

(WW, BB, BZBZ, CC, BW, CW, HW)




**6" Round Adjustable Reflector**

**ELK629**

Finishes:

(WW, BB, BZBZ, BW, CW, HW)



**6" Round Adjustable Baffle**


**ELK693**

Finishes:

(WW, BB, BZBZ, BW)

## 6" Unique™ Twist-On Trims

---




**6" Round Reflector**

**ELK6710**

Finishes:

(W, B, BZ)



**6" Round Baffle**

**ELK6713**

Finishes:

(W, BZ)



**6" Round Wall Wash**

**ELK6715**

Finishes:

(W, BZ)


Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B\*** - All Black (For ELK6710, ELK6713, ELK6715)

# Compatible Products

For use with **Koto™ LED Module**


## 2" Koto Sylo™ Build-Your-Own

---




2" Koto Sylo Housing  
**Surface Mount**

CAT NO.	SPECIFICATIONS
EKS25SFW	White Finish
EKS25SFB	Black Finish
EKS25SFS	Silver Finish




2" Koto Sylo Housing  
**Monopoint**

CAT NO.	SPECIFICATIONS
EKS25MPW	White Finish
EKS25MPB	Black Finish
EKS25MPS	Silver Finish



2" Koto Sylo Housing  
**Pendant**

CAT NO.	SPECIFICATIONS
EKS25PDW	White Finish
EKS25PDB	Black Finish
EKS25PDS	Silver Finish



2" Koto Sylo Housing  
**Surface Mount**


CAT NO.	SPECIFICATIONS
EKS25TRW	White Finish
EKS25TRB	Black Finish
EKS25TRS	Silver Finish

# Photometric Report

## Koto™ LED Module

### PHOTOMETRIC REPORT

Product #: ELK08CT5 @2700K  
Wattage / Lumens: 10.6W / 729.1 lm  
Luminaire LPW: 68.7 lm/W



### CANDLE POWER SUMMARY

Degree Vertical	0°
0	1700
5	1530
15	868
25	246
35	56
45	24
55	12
65	5
75	1
85	1
90	1

### ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	106.2	2.6'
6'	47.2	3.9'
8'	26.5	5.1'
10'	17.0	6.4'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	617.9	84.8
0-40°	674.3	92.5
0-60°	709.6	97.4
0-90°	718.9	98.7

### PHOTOMETRIC REPORT

Product #: ELK08CT5 @3000K  
Wattage / Lumens: 10.1W / 887.3 lm  
Luminaire LPW: 87.8 lm/W



### CANDLE POWER SUMMARY

Degree Vertical	0°
0	1904
5	1681
15	902
25	250
35	61
45	30
55	17
65	10
75	6
85	6
90	6

### ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	119	2.5'
6'	52.8	3.8'
8'	29.7	5.1'
10'	19.0	6.3'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	702.7	79.2
0-40°	771.5	87
0-60°	819.9	92.5
0-90°	845.8	95.4

### PHOTOMETRIC REPORT

Product #: ELK08CT5 @3500K  
Wattage / Lumens: 10.19W / 902.5 lm  
Luminaire LPW: 88.5 lm/W



### CANDLE POWER SUMMARY

Degree Vertical	0°
0	1999
5	1840
15	1126
25	372
35	83
45	35
55	20
65	11
75	7
85	6
90	6

### ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	124.9	2.6'
6'	55.5	3.8'
8'	31.2	5.1'
10'	20.0	6.4'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	720.4	79.9
0-40°	786.4	87.2
0-60°	835.1	92.6
0-90°	860.9	95.4

### PHOTOMETRIC REPORT

Product #: ELK08CT5 @4000K  
Wattage / Lumens: 10.4 W / 921 lm  
Luminaire LPW: 88.5 lm/W



### CANDLE POWER SUMMARY

Degree Vertical	0°
0	2025
5	1902
15	1198
25	409
35	90
45	36
55	21
65	13
75	8
85	7
90	7

### ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	126.5	2.6'
6'	56.2	3.9'
8'	31.6	5.2'
10'	20.25	6.5'

### ZONAL LUMEN SUMMARY


Zone	Lumens	%Luminaire
0-30°	729.7	79.3
0-40°	797.3	86.6
0-60°	847.7	92.1
0-90°	875.5	95.1

# Photometric Report

## Koto™ LED Module

### PHOTOMETRIC REPORT

Product #: ELK08CT5 @5000K  
 Wattage / Lumens: 10.6 W / 930.9 lm  
 Luminaire LPW: 87.8 lm/W



### CANDLE POWER SUMMARY

Degress Vertical	0°
0	1984
5	1790
15	1039
25	319
35	73
45	34
55	19
65	11
75	7
85	6
90	6

### ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	124	2.6'
6'	55.1	4.0'
8'	31.0	5.3'
10'	19.8	6.6'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	737.6	79.3
0-40°	810.6	87.1
0-60°	861.3	92.6
0-90°	888.0	95.4

### PHOTOMETRIC REPORT

Product #: ELK10CT5 @2700K  
 Wattage / Lumens: 12.6W / 908.8 lm  
 Luminaire LPW: 72 lm/W



### CANDLE POWER SUMMARY

Degress Vertical	0°
0	2015
5	1833
15	1076
25	313
35	69
45	31
55	17
65	9
75	5
85	4
90	4

### ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	125.9	2.6'
6'	55.9	4.0'
8'	31.4	5.3'
10'	20.1	6.6'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	741.7	81.7
0-40°	811.0	89.3
0-60°	858.8	94.5
0-90°	879.3	96.8

### PHOTOMETRIC REPORT

Product #: ELK10CT5 @3000K  
 Wattage / Lumens: 12W / 1013.2 lm  
 Luminaire LPW: 84.4 lm/W



### CANDLE POWER SUMMARY

Degress Vertical	0°
0	2241
5	2012
15	1152
25	341
35	77
45	35
55	20
65	11
75	7
85	5
90	6

### ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	140	2.6'
6'	62.2	3.8'
8'	35.0	5.1'
10'	22.4	6.4'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	816.5	80.6
0-40°	893.2	88.2
0-60°	947.2	93.5
0-90°	973.3	96.1

### PHOTOMETRIC REPORT

Product #: ELK10CT5-W @3000K  
 Wattage / Lumens: 12W / 1013.2 lm  
 Luminaire LPW: 84.4 lm/W



### CANDLE POWER SUMMARY

Degress Vertical	0°
0	803
5	816
15	812
25	656
35	409
45	202
55	73
65	22
75	8
85	2
90	2

### ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	50.2	4.9'
6'	22.3	7.4'
8'	12.5	9.8'
10'	8.03	12.3'

### ZONAL LUMEN SUMMARY


Zone	Lumens	%Luminaire
0-30°	577.9	58
0-40°	797.8	80.1
0-60°	971.5	97.5
0-90°	996.1	100

# Photometric Report

## Koto™ LED Module

### PHOTOMETRIC REPORT

Product #: ELK10CT5 @3500K  
 Wattage / Lumens: 11.9W / 1039.2 lm  
 Luminaire LPW: 87.3 lm/W



### CANDLE POWER SUMMARY

Degree Vertical	0°
0	2331
5	2126
15	1257
25	390
35	89
45	37
55	20
65	11
75	6
85	5
90	5

### ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	145.6	2.6'
6'	64.7	3.9'
8'	36.4	5.2'
10'	23.3	6.4'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	842.3	81.1
0-40°	919.7	88.5
0-60°	974.8	93.8
0-90°	1,000.8	96.4

### PHOTOMETRIC REPORT

Product #: ELK10CT5 @4000K  
 Wattage / Lumens: 12.19W / 1043.6 lm  
 Luminaire LPW: 85.6 lm/W



### CANDLE POWER SUMMARY

Degree Vertical	0°
0	2348
5	2177
15	1349
25	455
35	101
45	41
55	22
65	12
75	7
85	5
90	5

### ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	146.7	2.6'
6'	65.2	3.9'
8'	36.6	5.2'
10'	23.4	6.5'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	849.4	81.4
0-40°	926.5	88.8
0-60°	981.4	94.1
0-90°	1,006.3	96.5

### PHOTOMETRIC REPORT

Product #: ELK10CT5 @5000K  
 Wattage / Lumens: 12.3W / 1032.7 lm  
 Luminaire LPW: 83.9 lm/W



### CANDLE POWER SUMMARY

Degree Vertical	0°
0	2297
5	2078
15	1210
25	368
35	79
45	36
55	20
65	11
75	6
85	5
90	5

### ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	143.5	2.6'
6'	63.8	3.9'
8'	35.8	5.2'
10'	22.9	6.5'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	837.9	81.2
0-40°	917.0	88.8
0-60°	971.5	94.1
0-90°	996.1	96.5



**ELCO Lighting**

# Dimmer Compatibility Chart

## Standard Koto™ LED Modules

For ELK07, ELK08CT5, ELK09, ELK10CT5, ELK11 & ELK13 Series

### For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Leviton	Decora SureSlide® Single Pole with Slide -to-Off	6672	15% - 100%
	Leviton Dimmer	1K3502	5% - 100%
Lutron	Vive, 120V, 150W LED/CFL, 600W Incandescent/Halogen, FP, Single Pole/Multi-Location Dimmer, Commercial Application	MRF2S-6CL	12% - 91%
	Panel Model, Commercial/Residential Application, FP	GP (Harrier) Card	10% - 94%
	Grafik QS/Mailbox Power Module, 120/220 to 240V AC, LED/Incandescent/Halogen Load Type, Commercial/Residential Indoor Application, FP	LQRJ-WPM-6P	10% - 95%
	Grafik Eye 3000/HomeWorks, 120V, Incandescent/Fluorescent Load Type, Commercial/Residential Application, FP	HWI-WPM-6D-120	10% - 95%
	Panel Dimming Module, 120V, Commercial/Residential Application, FP	HW/LP-RPM-4U-120	10% - 95%
	Panel Adaptive Dimming Module, 120V, Commercial/Residential Application, FP	HW/LP-RPM-4A-120	9% - 95%
	HomeWorks® QS for CFL/LED loads, 120V, RP, Commercial/Residential Application	LQSE-4A1-D/MQSE-4A1-D/ MQSE-3A1/MQSE-2A1-D	8% - 95%
	Energi Savr Node LED+ Phase Adaptive, Commercial Application, Reverse Phase, (Zone 1) (Zones 2-4)	QSN-4A5-S	8% - 95%
	Energi Savr Node LED+ Phase Adaptive, Commercial Application, Forward Phase, (Zone 1) (Zones 2-4)	QSN-4A5-S	10% - 97%
	RadioRA®2, 120V, 50/60-Hz, 150W LED or 600W Incandescent/Halogen, 3-Way & 4-Way, Residential Application	RRD-6CL	10% - 95%
	RadioRA®3, 120V, 250W LED/CFL or 500W Incandescent/Halogen, Single Pole, Multi-Location	RRST-PRO-N	10% - 95%
	HomeWorks® QS, 120V, 60-Hz, 150W LED/CFL or 600W Incandescent/Halogen/MLV, Residential Application	HQRD-6CL(H2) HQRA-6CL(H2)	10% - 95%
	Homeworks QS, Residential Application, Reverse Phase	LQSE-4A-120-D	8% - 89%
	HomeWorks® for LED/Incandescent/Halogen loads, Reverse Phase, (Zone 1) (Zones 2-4)	LQSE-4A5-120-D	8% - 89%
	HomeWorks® for LED/Incandescent/Halogen loads, Forward Phase, (Zone 1) (Zones 2-4)	LQSE-4A5-120-D	10% - 100%
	Ariadni® C-L Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	AYCL-153P	10% - 100%
	Skylark Contour® C-L, Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	CTCL-153P	10% - 100%
Skylark® C-L Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	SCL-153P	10% - 100%	

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 [elcolighting.com](http://elcolighting.com)

Manufacturer	Product	Part Number	Dimmed Light Output Range
Lutron	Diva® Series 150W Single Pole/3-Way Dimmer	DVCL-153P	10% - 100%
	Skylark Contour® Single Pole/3-Way 1000W Incandescent/Halogen	CT-103P	10% - 100%
	Skylark® Single Pole 300W ELV Preset Dimmer	SELV-300P	5% - 100%
	Skylark® Single Pole 600W Incandescent/Halogen, Slide-to-Off Dimmer	S-600P	5% - 100%
	Diva® 300W Single Pole/3-Way ELV Dimmer	DVELV-303P	10% - 100%
	Diva® 600W Single Pole Incandescent/Halogen Preset Dimmer	DV-600P	5% - 100%
	Ariadni® 600W Single Pole Magnetic Low Voltage Dimmer	AYLV-600P	5% - 100%
	Ariadni® 600W Single Pole/3-Way Incandescent/Halogen Dimmer	AY-603P	5% - 100%
	Maestro® 600W Single Pole/3-Way ELV Dimmer	MAELV-600	5% - 100%
	Maestro® C-L Single Pole/3-Way Dimmer. 150W Max for LED/CFL or 600W Max for Incandescent/Halogen	MACL-153M	10% - 100%
	Caséta® Wireless Dimmer	PD-6WCL	10% - 100%
SnapOne™	Control4® Centralized 8-Channel Adaptive Phase Dimmer, 120/277V AC, 50/60-Hz, 200W LED, 500W Fluorescent/CFL, 1000W Incandescent/Halogen/ELV/MLV*	C4-DIN-8APD	5% - 100%
	Control4® Centralized 8-Channel Forward Phase Dimmer, 100/120V AC, 50/60-Hz, 200W LED, 500W Fluorescent/CFL, 1000W Incandescent/Halogen/MLV*	C4-DIN-8FPD	25% - 100%
	Control4® Wireless Adaptive Phase Dimmer, 120V AC, 50/60-Hz, 120W LED, 300W Fluorescent/CFL, 600W Incandescent/Halogen	C4-APD120	23% - 100%
	Control4® Forward Phase Dimmer, 120V AC, 50/60-Hz, 200W LED, 500W Fluorescent/CFL, 1000W Incandescent/Halogen	C4-FPD120	4% - 100%
	Control4® Essential Forward Phase Dimmer, 120V AC, 60-Hz, 300W LED, 300W Fluorescent/CFL, 600W Incandescent/Halogen	C4-V-FPD120	1% - 100%
*MLV each transformer must be loaded to at least 50% of its maximum load			

**\*NOTE: Refer to dimmer manufacturer’s documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com