

# Koto™ Module with 2" Pex™ Square Deep Reflector Trim



## Features

- Integrated 120V dimmable driver Triac/ELV
- Excellent color rendering 95+ CRI
- Works in 2" Koto Dedicated LED Housings
- Energy Star Certified
- Title 24 JA8-2019 Compliant
- Standard 38° Lens - Optional Lenses: 18° (EP731C), 25° (EP732C), 60° (EP734C)
- Optional: Louver (L45), Linear Lens (L46), Spread Lens (L47)
- Patented

## Specifications

<b>Wattage</b>	10W
<b>Lumens</b>	750 lm - 950 lm
<b>Voltage</b>	120V
<b>Color Temp.</b>	2700K - 4000K, Sunset K
<b>Dimmable</b>	Triac/ELV
<b>Lamp Type</b>	LED
<b>Beam Angle</b>	38° Standard. 18°, 25°, 60° Optional

## Options



All White



Black/White Ring



All Black

## Technical Details

**Optics:** Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

**Construction:** Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allow for efficient cooling.

**Trim:** Pex™ Square Reflector Diecast aluminum with a powder coated finish.

**Installation:** Twist-On design for toolless trim installation, for use with Koto™ trims only. Can be used in 2" Koto dedicated led housings with quick connect base.

**Compatible Housing:** Compatible with 2" Koto housings: EL276ICA

**Electrical:** Module connects to 120V power supply. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.


**LED Technology:** Extremely accurate Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixilation.

**Dimmability:** Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the Dimmer Compatibility List. Industry leading dimming that dims smoothly with no hot spots or flickering.

**Listings:** UL Listed for Damp Location. RoHS Compliant. Energy Star Certified. Title 24 JA8-2019 Compliant

**Warranty:** ELCO Products are built to last with a 5-year Limited Warranty.

## Dimensions



## Product Numbers

Description	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle
Koto LED Module	LED	750 lm	2700K	10W	120V	Triac/ELV	38° Standard. 18°, 25°, 60° Optional
			-				
			4000K, Sunset K				
Koto LED Module	LED	950 lm	2700K	10W	120V	Triac/ELV	38° Standard. 18°, 25°, 60° Optional
			-				
			4000K, Sunset K				

# Product Number Builder Example:


Module	Lumens	Color Temp.	-	Pex™ Trim
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<b>ELK</b> LED Module	<b>07</b> 750 lm <b>09</b> 950 lm	<b>27</b> 2700 <b>30</b> 3000 <b>35</b> 3500 <b>40</b> 4000 <b>SD</b> Sunset	-	<b>ELK2818</b> Round Reflector
<input type="text"/>				
<b>W</b> All White				
<b>B</b> Black/White Ring				
<b>BB</b> All Black				

## Product Custom Image

# Compatible Products

For use with 2" LED inserts


## 2" Koto™ Dedicated LED ICA Housings



2" ICA Maximum Adjustability Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL276ICA	Maximum Adjustability

## 2" Accessories



Emergency Battery Backup


CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V

\* Requires access from above



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L