

Koto™ Module with 2" Pex™ Square Gimbal Trim



Features

- Integrated 120V Dimmable Driver Triac/ELV
- Excellent color rendering 95+ CRI
- Works in 2" Koto Dedicated LED Housings
- Twist-On system for easy trim installation
- 30° tilt
- Energy Star Certified
- Title 24 JA8-2019 Compliant
- Standard 38° Lens - Optional Lenses: 18° (EP731C), 25° (EP732C), 60° (EP734C)
- Optional: Louver (L45), Linear Lens (L46), Spread Lens (L47)
- Patented

Specifications

Wattage	10W
Lumens	750 lm - 950 lm
Voltage	120V
Color Temp.	2700K - 4000K, SunsetK
Dimmable	Triac/ELV
Lamp Type	LED
Beam Angle	38° Standard. 18°, 25°, 60° Optional

Options



All White



All Bronze

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allow for efficient cooling.

Trim: Pex™ Square Adjustable Spot Diecast aluminum with a powder coated finish.

Installation: Twist-On design for toolless trim installation, for use with Koto™ trims only. Can be used in 2" Koto dedicated led housings with quick connect base.

Compatible Housing: Compatible with 2" Koto housings: EL276ICA

Electrical: Module connects to 120V power supply. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.


LED Technology: Extremely accurate Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixilation.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the Dimmer Compatibility List. Industry leading dimming that dims smoothly with no hot spots or flickering.

Listings: UL Listed for Damp Location. RoHS Compliant. Energy Star Certified. Title 24 JA8-2019 Compliant

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Dimensions



Product Numbers

Description	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle
Koto LED Module	LED	750 lm	2700K - 4000K, SunsetK	10W	120V	Triac/ELV	38° Standard. 18°, 25°, 60° Optional
Koto LED Module	LED	950 lm	2700K - 4000K, SunsetK	10W	120V	Triac/ELV	38° Standard. 18°, 25°, 60° Optional

Product Number Builder Example:


Module	Lumens	Color Temp.	-	Pex™ Trim
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
ELK LED Module	07 750 lm 09 950 lm	27 2700 30 3000 35 3500 40 4000 SD Sunset	-	ELK2588 Pex 2" Square Adj. Spot
<input type="text"/>				
W All White BZ All Bronze				

Product Custom Image

Compatible Products

For use with 2" LED inserts


2" Koto™ Dedicated LED ICA Housings



2" ICA Maximum Adjustability Housing
New Construction

CAT NO.	SPECIFICATIONS
EL276ICA	Maximum Adjustability

2" Accessories



Emergency Battery Backup


CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V

* Requires access from above



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L