

LED Adjustable Emergency Light




Features

- Emergency Light with two Adjustable 1.5W LED glare free light heads.
- 120/277V.
- Universal mounting plate for fast and easy installation.
- Sturdy thermoplastic housing.
- Automatic switching from AC supply to battery power.
- Long life NiCad battery.
- cUL Listed for damp location.

Specifications

Wattage	3W
Voltage	120/277V

Dimensions



Product Numbers


Item	Watts	Voltage	Finish
EE22L	3W	120/277V	All White

Photometric Report

LED Adjustable Emergency Light

PHOTOMETRIC REPORT

Product #: EE22L
 Wattage / Lumens: 1.40W / 131.5 lm
 Luminaire LPW: 93.9 lm/W



CANDLE POWER SUMMARY

Degree Vertical	0°
0	512
5	388
15	149
25	46
35	20
45	9
55	5
65	3
75	1
85	1
90	0

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	32.0	1.5'
6'	14.2	2.2'
8'	8.00	2.9'
10'	5.12	3.7'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	101.5	77.1
0-40°	114.2	86.7
0-60°	126.7	96.2
0-90°	131.7	100