

LED Area and Site Light

Durable diecast LED area and site lights. High efficiency LED and optics for energy efficient performance and uniform light distribution.



Features

- Diecast housing with advanced thermal heat dissipation
- Input voltage 120-277V AC
- Standard 0-10V Dimming
- Slipfitter and wallmounting accessories available
- PIR motion sensor and Photocell available
- Wet Location Rated

Small: 40W&70W&100W Dimensions: 20" x 8.5" x 7"

Medium: 150W&200W Dimensions: 21.1" x 12.25" x 7"

Large: 250W&300W Dimensions: 30.25" x 12.25" x 7"

Technical Details

Lamp: SMD LED, CRI 80+

Optics: Shatterproof polycarbonate lens diffuses light evenly throughout space.

Construction: Die-cast aluminum housing. Impact, corrosion, and UV resistant.

Installation: Slipfitter and wallmounting accessories available

Electrical: Constant current 120-277V AC Class 2 Driver with a power factor > 0.9. Ambient operating temperature: -40°F (-40°C) to 113°F (45°C).

Listings: UL Listed for wet location. IP65 rated.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years.

Options



Square Pole Mount



Slipfitter Mount



Wall Mount



Yoke Mount

Product Numbers

Product Number Builder Example:

Area Light	Wattage/Size	Color Temp	Mounting Style
EAL			
	45S 45W Small	40 4000K	SPM Square Pole Mount
	70S 70W Small	50 5000K	RPM Round Pole Mount
	100S 100W Small		SLM Slipfitter Mount
	150M 150W Medium		WM Wall Mount
	200M 200W Medium		YKM Yoke Mount
	250L 250W Large		
	300L 300W Large		