

LED Area and Site Light

Durable diecast LED area and site lights. High efficiency LED and optics for energy efficient performance and uniform light distribution.



Features

- Diecast housing with advanced thermal heat dissipation
- Input voltage 120-277V AC
- Standard 0-10V Dimming
- Slipfitter and wallmounting accessories available
- PIR motion sensor and Photocell available
- Wet Location Rated

Small: 40W&70W&100W Dimensions: 20" x 8.5" x 7"

Medium: 150W&200W Dimensions: 21.1" x 12.25" x 7"

Large: 250W&300W Dimensions: 30.25" x 12.25" x 7"

Technical Details

Lamp: SMD LED, CRI 80+

Optics: Shatterproof polycarbonate lens diffuses light evenly throughout space.

Construction: Die-cast aluminum housing. Impact, corrosion, and UV resistant.

Installation: Slipfitter and wallmounting accessories available

Electrical: Constant current 120-277V AC Class 2 Driver with a power factor > 0.9. Ambient operating temperature: -40°F (-40°C) to 113°F (45°C).

Listings: UL Listed for wet location. IP65 rated.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years.

Options



Square Pole Mount



Slipfitter Mount



Wall Mount



Yoke Mount

Product Numbers

Product Number Builder Example:

Area Light	Wattage/Size	Color Temp	Mounting Style
EAL			
	40S 40W Small 70S 70W Small 100S 100W Small 150M 150W Medium 200M 200W Medium 250L 250W Large 300L 300W Large	50 5000K	SPM Square Pole Mount RPM Round Pole Mount SLM Slipfitter Mount WM Wall Mount YKM Yoke Mount