

Project name:	
Fixture type:	
Date:	

LED Cleat™ Track Fixture



Features

- Solid diecast aluminum fixture
- Integrated driver
- 180º tilt, 358º rotation
- 50,000 hours life-span
- 38º Beam Angle Standard. Optional Lenses: EP719C (15º) or EP720C (24º) available
- This track head comes standard as H Style.
 J (Juno) and L (Lightolier) styles are available:
 For J style please order PJTHI (W/B) with the track head.

For L style please order PLTHI (W/B) with the track head.

Note these must be factory installed.

Specifications

Wattage	10W - 13W
Lumens	700 lm - 1000 lm
Voltage	120V
Color Temp.	3000K
Dimmable	Yes
Lamp Type	LED
Beam Angle	38°

Technical Details

Construction: Full diecast construction for exceptional heat management and lasting quality. Powder coat architectural white and architectural black matte finishes.

Adjustability: Track head is adjustable 90° tilt with 358° rotation.

Optics: Lens provides smooth lumen output at standard 38°. Optional Lenses: EP719C (15°) or EP720C (24°) available.

Installation: Effortlessly installed into H-Style track from ELCO or others. Compatible with Single and Double circuit track. Can be special ordered as J-Style (requires PJTLO W/B/) or L-Style (requires PLTLO W/B).

LED Technology:

- Extremely accurate Color Rendering Index of 90+ CRI
- Efficacy of over 81 lumens per watt
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results
- Instant On to Full Brightness technology
- Chip on Board LED design results in a smooth lumen output with no LED pixelation

Dimmability:

- $\bullet~$ Triac and ELV dimmable down to 10%
- Flicker-Free Dimming
- For full list of dimmers refer to the Dimmer Compatibility List

Electrical:


Options





White

Dimensions



Product Numbers

Item	Lamp type	Lumens	сст	Watts	Voltage	Dimming	Beam Angle	Finish
ET62530DW	LED	700 lm	3000K	10W	120V	Yes	38°	All White
ET62530DB	LED	700 lm	3000K	10W	120V	Yes	38°	All Black
ET62630DW	LED	1000 lm	3000K	13W	120V	Yes	38°	All White
ET62630DB	LED	1000 lm	3000K	13W	120V	Yes	38°	All

- Driver is rated for 120V input
 High Efficiency driver with a power factor > 0.9

 $\textbf{Listings} \hbox{: } \mathsf{ETL} \ \mathsf{Listed}. \ \mathsf{RoHS} \ \mathsf{Compliant}$


Warranty: ELCO Products are built to last. 5-year Limited warranty.

Photometric Report

LED Cleat™ Track Fixture

PHOTOMETRIC REPORT

Product #: ET62530D Wattage / Lumens: 10W / 706.3 lm Luminaire LPW: 70.6 lm/W



Degress Vertical	0°	
0	1827	
5	1675	
15	925	
25	305	
35	89	
45	35	
55	15	
65	6	
75	1	
85	0	

0

CANDLE POWER SUMMARY

ILLUMINANCE AT A DISTANCE


	Distance to Target Plane	Center Beam Footcandles	Beam Diameter	
	4'	158	2.1′	
	6′	55.5	3.1′	
	8′	28.5	4.3'	
98	10′	19.2	5.3′	

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	593.6	83.2
0-40°	659.9	92.5
0-60°	704.4	98.7
0-900	713.1	99.9

PHOTOMETRIC REPORT

Product #: ET62630D Wattage / Lumens: 13W / 1000 lm Luminaire LPW: 76.9 lm/W



CANDLE POWER SUMMARY

90

Degress Vertical

ILLUMINANCE AT A DISTANCE

9	137	
0	2560	
5	2348	5000
15	1296	
25	428	
35	124	z
45	48	
55	21	
65	8	
75	2	
85	1	
90	0	100

	Distance to Target Plane	Center Beam Footcandles	Beam Diameter	
992	4′	221	2.1′	
	6′	77.8	3.1′	
	8′	40.0	4.3'	
3	10′	26.9	5.3′	

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	832.2	83.2
0-40°	925	92.5
0-60°	987.3	98.7
0-90°	999.5	99.9