

LED Emergency Light




Features

- Mini Emergency Light with two 2W fully adjustable glare-free square shape light heads for emergency light.
- Injection-molded thermoplastic ABS housing Innovative snap-together design allows for fast and easy installation.
- 250 lm (total) 3.6V, 1.5Ah battery pack for 90 minutes of emergency operation.
- LED Driver: 120V/277V AC, dual voltage operation integrated with LED bulb.
- cUL listed for damp location.

Specifications

Wattage	4W
Voltage	120/277V

Dimensions



Product Number


Item	Watts	Voltage
EE80L	4W	120/277V

Photometric Report

LED Emergency Light

PHOTOMETRIC REPORT

Product #: EE80L
 Wattage / Lumens: 1.80W / 149.9 lm
 Luminaire LPW: 83.2 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	408
5	327
15	149
25	57
35	28
45	14
55	9
65	6
75	3
85	1
90	1

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	25.5	1.8'
6'	11.3	2.7'
8'	6.37	3.6'
10'	4.08	4.4'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	106.1	70.7
0-40°	124.0	82.6
0-60°	142.2	94.7
0-90°	150.1	100