

Project	name:
Fixture	type:

Date:

LED Small Wall Packs

This small-sized LED wall pack features a traditional design, but with energy efficient performance. Die-cast aluminum housing ensures long lasting functionality. High quality polycarbonate lens guards against vandalism and environmental contamination.




Features

- Non-Dimmable LED Small Wall Pack.
- Die-cast Aluminum Housing, polycarbonate lens.
- Easily removed mounting knockouts and J-box pattern panel plate.
- J-box or direct wall mount for surface conduit (back mount).

Specifications

Wattage	30W
Lumens	3800 lm - 3900 lm
Voltage	120/277V
Color Temp.	4000K - 5000K
Lamp Type	LED
Power Factor	>0.9
Wet Location	Listed

Dimensions



Technical Details

Lamp: SMD LED, CRI 80+

Optics: Shatterproof polycarbonate lens.

Construction: Die-cast aluminum housing with dark bronze powder coated finish.

Impact and corrosion resistant.

Installation: 3/4" knockout points on the side and top for surface conduit supply or photocell connection.

Hinges for easy installation.

Electrical: Constant current 120/277V AC Class 2 Driver with a power factor > 0.9. Ambient operating

temperature: -40°F (-40°C) to 113°F (45°C).

Dimmability (Optional): Works with 0-10V type dimmers. For full list of dimmers, refer to the dimmer

compatability list.

Listings: cUL listed for wet location. DLC listed. LM-80 certified. IP65 rated.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years.

Product Numbers

Item	Lamp type	Lumens	сст	Watts	Voltage	Finish
EWP30S40	LED	3800 lm	4000K	30W	120/277V	All Bronze
EWP30S50	LED	3900 lm	5000K	30W	120/277V	All