

Lotus II™ LED Undercabinet Light



Features

- Mini linking connector included for row mounting
- Individually switch with pass-through power
- 2700K/3000K/3500K (CCT Switch)
- Linkable end-to-end On/Off switch
- Polycarbonate lens
- Dimmable driver included
- Hard wire or plug & play
- cUL listed
- 120V
- High CRI 90
- T24 JA8-2016 Compliant

Specifications


Wattage	6W - 18W
Lumens	360 lm - 1100 lm
Voltage	120V
Color Temp.	2700K, 3000K, 3500K
Lamp Type	LED

Options



White

Dimensions



Product Numbers

Item	Description	Lamp type	Lumens	CCT	Watts	Voltage	Finish
EU3T08W	8" Length	LED	360 lm	2700K, 3000K, 3500K	6W	120V	All White
EU3T12W	12" Length	LED	485 lm	2700K, 3000K, 3500K	8W	120V	All White
EU3T16W	16" Length	LED	610 lm	2700K, 3000K, 3500K	10W	120V	All White
EU3T24W	24" Length	LED	850 lm	2700K, 3000K, 3500K	14W	120V	All White
EU3T32W	32" Length	LED	1100 lm	2700K, 3000K, 3500K	18W	120V	All White

Product Number Builder Example: **EU3T08W**

Lotus 2™ Undercab. Bar

Length

Finish

EU3T

- 08** 8 in
- 12** 12 in
- 16** 16 in
- 24** 24 in
- 32** 32 in

W All White



Dimmer Compatibility Chart for Lotus II™ Undercabinet Lights

ELCO Lighting

EU3T Series

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
GE	Single Pole Rocker-Style Dimmer Switch	10464	10% - 100%
	Toggle-Style On/Off with Slide Lighted Dimmer	18027	10% - 100%
Leviton	Decora 4-Level Step Electro-Mechanical Incandescent Dimmer	6161-A	10% - 100%
	IllumaTech Slide Dimmer for 150-Watt Dimmable LED/CFL, 600-Watt Incandescent/Halogen	IPL06-10Z	10% - 100%
	IllumaTech 1000W Preset Incandescent Dimmer, Single Pole or 3-Way	IPI0-1LZ	10% - 100%
	IllumaTech 600W Preset Single-Pole & 3-Way Electro-Mechanical Incandescent Slide Dimmer	IPI06-1LZ	10% - 100%
	Decora SureSlide Universal LED Dimmer 60Hz Single Pole/3-Way	6674	10% - 100%
	SureSlide 150W LED/CFL Incandescent Slide-To-Off Dimmer	6672-1LW	10% - 100%
	SureSlide 600W Decora Full Range Slide Dimmer	6633-POG	10% - 100%
	Trimatron 600W Single Pole Electro-Mechanical Rotary Dimmer with Push On/Off Switch	6681	10% - 100%
	Dimmer Lamp Socket 150W Incandescent Single-Pole	6151	10% - 100%
	SureSlide Incandescent Slide Dimmer	6633-I	10% - 100%
Lutron	Maestro® Series 150W Single Pole/3-Way/Multi-Location Dimmer	MACL-153MR-WH	10% - 100%
	Maestro® Series 150W Single Pole/3-Way/Multi-Location Dimmer	MACL-153P	10% - 100%
	Skylark® 150W Single Pole/3-Way Dimmer	SCL-153PR-WH	5% - 86%
	Ariadni®/Toggler® Series 150W Single Pole/3-Way Dimmer	TGCL-153P	10% - 100%
	DIVA® Series 150W Single Pole/3-Way Dimmer	DVCL-153P	10% - 100%
	Skylark Contour® 150W Single Pole/3-Way Dimmer	CTCL-153P	10% - 100%
	Lumea C•L Dimmer - 150W LED/600W Incandescent/Halogen	LGCL-153P	10% - 100%
	Nova® Single Pole Incandescent/Halogen Slide-to-Off Dimmer	N-600	10% - 100%
	Skylark® Single Pole/3-Way, Incandescent/Halogen, Preset, "Eco-Dim" Dimmer	S-603PG	5% - 85%
	Skylark Contour 300W Electronic Low Voltage Single Pole/3-Way	CTELV-303P-WH	10% - 100%
	Skylark 150-Watt Single-Pole/3-Way Dimmer	SCL-153-LA	10% - 100%
	Ariadni®/Toggler® Series 150W Single Pole/3-Way Dimmer	TGCL-153P	5% - 86%

2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.