

Lotus™ LED Undercabinet Light



Features

- Slim LED Undercabinet Light with mini linking connector included for row mounting, linkable end-to-end.
- Solid aluminum construction with white polycarbonate lens.
- Knockout on back and bottom for easy access to wiring compartment, hardwire installation or plug and play.
- ON/OFF switch, individually switched with pass-through power.
- Captive screws for easy mounting.
- Lamp: LED CREE array chip.
- LED Driver: 120V AC, dimmable (included).
- CA Title 24 compliant (JA8-2016).
- cUL Listed.
- Life span of 35,000 hours L70

Specifications

| | |
|--------------------|---|
| Wattage | 14WW - 19.5W |
| Lumens | 350 lm - 4000 lm |
| Voltage | 120V |
| Color Temp. | 2700K, 3000K, 3500K, 4000K, 5000K - 4000K |
| Dimmable | Triac/ELV |
| Lamp Type | LED |


Options



Bronze

White

Dimension



Product Numbers

| Item | Description | Lamp Type | Lumens | CCT | Watts | Voltage | Dimming | Finish |
|------------|-------------|-----------|---------|-----------------------------------|-------|---------|-----------|------------|
| EUB11L30BZ | 11" Length | LED | 350 lm | 3000K | 5.5W | 120V | Triac/ELV | All Bronze |
| EUB11L40BZ | 11" Length | LED | 350 lm | 4000K | 5.5W | 120V | Triac/ELV | All Bronze |
| EUB11CT5W | 11" Length | LED | 350 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 5.5W | 120V | Triac/ELV | All White |
| EUB12L30W | 12" Length | LED | 400 lm | 2700K, 3000K, 4000K | 6W | 120V | Triac/ELV | All White |
| EUB12L30BZ | 12" Length | LED | 400 lm | 2700K, 3000K, 4000K | 6W | 120V | Triac/ELV | All Bronze |
| EUB12CT5W | 12" Length | LED | 400 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 6W | 120V | Triac/ELV | All White |
| EUB14L30W | 14" Length | LED | 480 lm | 2700K, 3000K, 4000K | 7W | 120V | Triac/ELV | All White |
| EUB14L30BZ | 14" Length | LED | 480 lm | 3000K | 7W | 120V | Triac/ELV | All Bronze |
| EUB14L40W | 14" Length | LED | 4000 lm | 4000K | 7W | 120V | Triac/ELV | All White |
| EUB14L40BZ | 14" Length | LED | 480 lm | 4000K | 7W | 120V | Triac/ELV | All Bronze |
| EUB18L30BZ | 18" Length | LED | 650 lm | 3000K | 9.2W | 120V | Triac/ELV | All Bronze |

| Item | Description | Lamp type | Lumens | CCT | Watts | Voltage | Dimming | Finish |
|-------------------|-------------|-----------|---------|---|-------|---------|-----------|------------|
| EUB18CT5W | 18" Length | LED | 650 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 9W | 120V | Triac/ELV | All White |
| EUB22L40BZ | 22" Length | LED | 700 lm | 4000K | 9.6W | 120V | Triac/ELV | All Bronze |
| EUB22CT5W | 22" Length | LED | 700 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 10.5W | 120V | Triac/ELV | All White |
| EUB29L40BZ | 29" Length | LED | 900 lm | 4000K | 12.2W | 120V | Triac/ELV | All Bronze |
| EUB29CT5W | 29" Length | LED | 900 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 12.2W | 120V | Triac/ELV | All White |
| EUB32CT5W | 32" Length | LED | 1000 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 14W | 120V | Triac/ELV | All White |
| EUB36L30BZ | 36" Length | LED | 1150 lm | 3000K | 15.3W | 120V | Triac/ELV | All Bronze |
| EUB36L40BZ | 36" Length | LED | 1150 lm | 4000K | 15.3W | 120V | Triac/ELV | All Bronze |
| EUB36CT5W | 36" Length | LED | 1100 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 15.3W | 120V | Triac/ELV | All White |
| EUB48L30BZ | 48" Length | LED | 1450 lm | 3000K | 19.5W | 120V | Triac/ELV | All Bronze |
| EUB48L40W | 48" Length | LED | 1450 lm | 4000K | 19.5W | 120V | Triac/ELV | All White |
| EUB48L40BZ | 48" Length | LED | 1450 lm | 4000K | 19.5W | 120V | Triac/ELV | All Bronze |
| EUB48CT5W | 48" Length | LED | 1450 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 19.5W | 120V | Triac/ELV | All White |

Compatible Products

Lotus™ LED Undercabinet Light



Accessories




Linking Connectors

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EUBC03 | 3" Length |
| EUBC06 | 6" Length |
| EUBC012 | 12" Length |
| EUBC024 | 24" Length |



5' Power Cord

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EUBCRD | 5' Length |



J-Box for Hard Wire Supply Connection

| CAT NO. | SPECIFICATIONS |
|----------|----------------|
| EUBJBX | White |
| EUBJBXBZ | Bronze |



ELCO Lighting

Dimmer Compatibility Chart

Lotus™ LED Undercabinet Lights

For EUB11, EUB12, EUB14, EUB18, EUB22, EUB29, EUB32, EUB36, EUB42, and EUB48 Series

For Reference Only


Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

| Manufacturer | Product | Part Number | Dimmed Light Output Range |
|--------------|--|------------------------|---------------------------|
| Lutron | Skylark Contour, 120V AC, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way Indoor Application, Residential/Commercial Application | CT-603PG / CT-600PR | 10% - 100% |
| | Diva, 120V AC, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way, Residential/Commercial Application | DV-600PR / DV603PG | 10% - 100% |
| | Diva, 120V, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way | DVW-603PGH / DVCL-153P | 10% - 100% |
| | Maestro, 120V, 50/60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way | MACL-153M / TGCL-153P | 10% - 100% |
| | Skylark, Single Pole 600W Incandescent/Halogen, Slide-to-Off Dimmer | S-600PR / S-2-LH | 10% - 100% |
| Leviton | | 1A1505 / IC1605 | 10% - 100% |
| | SureSlide, 120V AC 60Hz, 600W for LED and CFL, 600W for Incandescent, Single Pole, 3-Way, Polycarbonated Housing | 6631 / 6633 | 10% - 100% |
| Cooper | Decorator Dimmer, 120V 60Hz, 300W for LED and CFL, 600W for Incandescent, Single Pole, 3-Way, Polycarbonated Housing | DLC03P | 10% - 100% |

***NOTE: Refer to dimmer manufacturer’s documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com