

# Mini LED Step Light

Horizontal or Vertical




## Features

- Adaptive Diecast Aluminum faceplate design allows for Vertical or Horizontal orientation.
- Powder Coated Faceplate
- Vertical or Horizontal Mounting
- Integrated LED board and driver
- Diffused lens behind faceplate
- Wet location listed for outdoor use
- IC Rated for direct contact with insulation
- Mounts in a standard single gang box
- Life span of 50,000 hours L70
- Input Voltage: 120V

## Specifications

<b>Wattage</b>	2.5W
<b>Lumens</b>	50 lm
<b>Voltage</b>	120V
<b>Color Temp.</b>	3000K
<b>Lamp Type</b>	LED
<b>CRI</b>	90+

## Options


**White**

**Black**

**Bronze**

**Nickel**

## Technical Details

**Optics:** Frosted lens diffuses light and illuminates walkway.

**Construction:** Diecast Faceplate with smooth powder coat finish. LED board and driver integrated in housing. Security screws for mounting faceplate to box included.

**Installation:** Easily installs into a standard single gang switch box.

### Electrical:


- Ambient operating temperature -23°F (-5°C) to 113°F (45°C).
- 120V ELST95: Driver input of 120V 50/60Hz connects directly to line voltage power.
- 12V ELST91: Input of 12V requires an external transformer.

### LED Technology:

- 90+ CRI for extremely accurate color rendering.
- Lumen Maintenance of 50,000 hours L70 Life.
- LED Array.

**Listings:** cETLus listed for Wet Location.

## Dimensions



## Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Finish
<b>ELST9930W</b>	LED	50 lm	3000K	2.5W	120V	All White
<b>ELST9930B</b>	LED	50 lm	3000K	2.5W	120V	All Black
<b>ELST9930N</b>	LED	50 lm	3000K	2.5W	120V	Nickel
<b>ELST9930BZ</b>	LED	50 lm	3000K	2.5W	120V	All Bronze

**Product Number Builder** Example: **ELST9930W**

---

Indoor Mini LED Step Light

Color Temp.

Finish

**ELST99**

**30** 3000K

**W** All White  
**B** All Black  
**BZ** All Bronze  
**N** Nickel