

Mini LED Step Light

Horizontal or Vertical



Features

- Adaptive Diecast Aluminum faceplate design allows for Vertical or Horizontal orientation.
- Powder Coated Faceplate
- Vertical or Horizontal Mounting
- Integrated LED board and driver
- Diffused lens behind faceplate
- Wet location listed for outdoor use
- IC Rated for direct contact with insulation
- Mounts in a standard single gang box
- Life span of 50,000 hours L70
- Input Voltage: 120V


Specifications

Wattage	2.5W
Lumens	50 lm
Voltage	120V
Color Temp.	3000K
Lamp Type	LED
CRI	90+

Options




White



Black



Bronze



Nickel

Technical Details

Optics: Frosted lens diffuses light and illuminates walkway.

Construction: Diecast Faceplate with smooth powder coat finish. LED board and driver integrated in housing. Security screws for mounting faceplate to box included.

Installation: Easily installs into a standard single gang switch box.

Electrical:


- Ambient operating temperature -23°F (-5°C) to 113°F (45°C).
- 120V ELST95: Driver input of 120V 50/60Hz connects directly to line voltage power.
- 12V ELST91: Input of 12V requires an external transformer.

LED Technology:

- 90+ CRI for extremely accurate color rendering.
- Lumen Maintenance of 50,000 hours L70 Life.
- LED Array.

Listings: cETLus listed for Wet Location.

Dimensions



Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Finish
ELST9930W	LED	50 lm	3000K	2.5W	120V	All White
ELST9930B	LED	50 lm	3000K	2.5W	120V	All Black
ELST9930N	LED	50 lm	3000K	2.5W	120V	Nickel
ELST9930BZ	LED	50 lm	3000K	2.5W	120V	All Bronze

Product Number Builder Example: **ELST9930W**

Indoor Mini LED Step Light

Color Temp.

Finish

ELST99

30 3000K

W All White
B All Black
BZ All Bronze
N Nickel