


Mini LED Step Light

Horizontal or Vertical




Features

- Adaptive Diecast Aluminum faceplate design allows for Vertical or Horizontal orientation.
- Powder Coated Faceplate
- Vertical or Horizontal Mounting
- Integrated LED board and driver
- Diffused lens behind faceplate
- Wet location listed for outdoor use
- IC Rated for direct contact with insulation
- Mounts in a standard single gang box
- Life span of 50,000 hours L70
- Input Voltage: 120V

Specifications

Wattage	2.5W
Lumens	50 lm
Voltage	120V
Color Temp.	3000K
Lamp Type	LED
CRI	90+

Options


White

Black

Bronze

Nickel

Technical Details

Optics: Frosted lens diffuses light and illuminates walkway.

Construction: Diecast Faceplate with smooth powder coat finish. LED board and driver integrated in housing. Security screws for mounting faceplate to box included.

Installation: Easily installs into a standard single gang switch box.

Electrical:


- Ambient operating temperature -23°F (-5°C) to 113°F (45°C).
- 120V ELST95: Driver input of 120V 50/60Hz connects directly to line voltage power.
- 12V ELST91: Input of 12V requires an external transformer.

LED Technology:

- 90+ CRI for extremely accurate color rendering.
- Lumen Maintenance of 50,000 hours L70 Life.
- LED Array.

Listings: cETLus listed for Wet Location.

Dimensions



Product Number

Item	Lamp type	Lumens	CCT	Watts	Voltage	Finish
ELST9930N	LED	50 lm	3000K	2.5W	120V	Nickel

Product Number Builder Example: **ELST9930W**

Indoor Mini LED Step Light

Color Temp.

Finish

ELST99

30 3000K

W All White
B All Black
BZ All Bronze
N Nickel