

Oak™ Housings with 12V AC Transformer




Features

- R60 Insulation housing, IC Airtight
- Includes individual electronic transformer
- 2" cutout for downlight E1L02, E1L12 and E11F
- 2 3/8" cutout for adjustable (E1L32 & E2L22) and trimless (EL01SFR + E1L61)
- Suitable for Chicago Plenum construction


Specifications

Voltage	120V or 277V
Dimmable	ELV, 0-10V

E1LF1



E1LF2



Product Numbers

Item	Description	Voltage	Dimming
E1LF1CAJ	For Oak Downlight	120V	ELV
E1LF1CAJ-7	For Oak Downlight	277V	
E1LF1CAJDX	For Oak Downlight	120V	0-10V
E1LF1CAJDX-7	For Oak Downlight	277V	0-10V
E1LF2CAJ	For Oak Adjustable	120V	ELV
E1LF2CAJ-7	For Oak Adjustable	277V	
E1LF2CAJDX	For Oak Adjustable	120V	0-10V
E1LF2CAJDX-7	For Oak Adjustable	277V	0-10V

Product Number Builder

Example: **E1LF1CAJ**

Elco Oak™ Mounting Frame

E1LF

Cutout

- 1** For Oak Downlight
- 2** For Oak Adjustable

IC Airtight

ICAJ ICA

Dimming

- 120V Input/ELV Dimmable
- 7** 277V Input
- DX** 120V Input/0-10V Dimmable
- DX-7** 277V Input/0-10V Dimmable

Compatible Products



For use with 1" Oak™ IC Rated R60 Insulation Housing

1" Oak™ Recessed Downlight LED Light Engines - use with E1LF1CAJ Series



E1L02 Series
Round Downlight
Finishes:
(W, B, BZ, H, BB)



E1L12 Series
Square Downlight
Finishes:
(W, B, BZ, H, BB)




E111
Cove Light
Finishes:
(W)

1" Oak™ Recessed Adjustable LED Light Engines - use with E1LF2CAJ Series



E1L32 Series
Round Gimbal
Finishes:
(W, B, BZ)



E1L22 Series
Square Pull Down
Finishes:
(W, B, BZ)

PRODUCT NUMBER BUILDER

Oak™ Light Engine	Style	Beam Angle	Color Temperature	Finish
E1L				
02	Round Downlight	F 38° (Standard)	27 2700K	W All White
12	Square Downlight	NF 28°	30 3000K	B Black
32	Round Gimbal	WF 60°	35 3500K	BZ All Bronze
22	Square Pull Down		40 4000K	H Haze w/White Ring
				BB All Black

Compatible Products

For use with 1" Oak™ IC Rated R60 Insulation Housing

1" Oak™ Accessories



Downlight Trims
For E1L02 & E1L12



Downlight Trims
For E1L02 & E1L12



Optional Lenses for
E1L02, E1L12, & E1L32

CAT NO.	SPECIFICATIONS
RM1W	All White
RM1B	Black w/ White Ring
RM1BZ	All Bronze
RM1H	Haze w/ White Ring
RM1BB	All Black

CAT NO.	SPECIFICATIONS
RM11W	All White
RM11B	Black w/ White Ring
RM11BZ	All Bronze
RM11H	Haze w/ White Ring
RM11BB	All Black

CAT NO.	SPECIFICATIONS
EP713C	28°
EP715C	50°