

PAR 30 Line Voltage Par Classic Track Fixture



Features

- For use with 1 or 2 circuit track and accessories.
- Adjustable lampholder.
- Lamp: 120V 75W PAR30.
- This track head comes standard as H Style. J (Juno) and L (Lightolier) styles are available: For J style please order PJTHI (W/B) with the track head.

For L style please order PLTHI (W/B) with the track head.
Note these must be factory installed.

Specifications

| | |
|------------------|-------------------|
| Wattage | 75W |
| Voltage | 120V |
| Lamp Type | Medium Base (E26) |

Options



Gold

Technical Details

Construction: Meticulously manufactured track fixture with a clean powder coated finish for lasting quality.

Adjustability: Track head is adjustable 180° vertically with 358° rotation.

Lamp: Compatible with LED and non-LED PAR30 lamp (not included).

Installation: Effortlessly installed into H-Style track from ELCO or others. Compatible with Single and Double circuit track. Can be special ordered as J-Style (requires PJTLO W/B/) or L-Style (requires PLTLO W/B).


Socket: High quality Porcelain socket, jacketed aluminum screw shell, medium-base (E26) socket.

Dimmability: Triac and ELV dimmable based on lamp.

Listings:

- ETL Listed
- RoHS Compliant

Dimensions



Product Numbers

| Item | Lamp type | Watts | Voltage | Finish |
|--------|-------------------|-------|---------|--------|
| ET695G | Medium Base (E26) | 75W | 120V | Gold |

Single Circuit



Single Circuit Track

Track supplied with dead end and mounting hardware

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP002W | White / 2' |
| EP004W | White / 4' |
| EP006W | White / 6' |
| EP008W | White / 8' |
| EP012W | White / 12' |
| EP002B | Black / 2' |
| EP004B | Black / 4' |
| EP006B | Black / 6' |
| EP008B | Black / 8' |
| EP0012B | Black / 12' |
| EP002BZ | Bronze / 2' |
| EP004BZ | Bronze / 4' |
| EP006BZ | Bronze / 6' |
| EP008BZ | Bronze / 8' |
| EP002N | Nickel / 2' |
| EP004N | Nickel / 4' |
| EP006N | Nickel / 6' |
| EP008N | Nickel / 8' |



Live End Connector

Live end connector used for direct wiring

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP801W | White |
| EP801B | Black |
| EP801BZ | Bronze |
| EP801N | Nickel |



Flexible Connector

Flexible connector to join two track sections at an angle up to 90°. Can be used as a feed point

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP802W | White |
| EP802B | Black |
| EP802BZ | Bronze |
| EP802N | Nickel |



Straight Connector

Power feedable connector to join two track sections

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP803W | White |
| EP803B | Black |
| EP803BZ | Bronze |
| EP803N | Nickel |



L Connector

Power feedable connector to join two track sections at a 90° angle

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP804W | White |
| EP804B | Black |
| EP804BZ | Bronze |
| EP804N | Nickel |



T Connector

Power feedable connector to join three track sections

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP805W | White |
| EP805B | Black |
| EP805BZ | Bronze |
| EP805N | Nickel |



X Connector

Power feedable connector to join four track sections

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP806W | White |
| EP806B | Black |
| EP806BZ | Bronze |
| EP806N | Nickel |



Mini Connector

Mini Connector to join two track sections. Cannot be used as a feed point


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP808W | White |
| EP808B | Black |
| EP808BZ | Bronze |
| EP808N | Nickel |



Floating Canopy

Can be used anywhere along length of track to supply power. Includes end cap

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP809W | White |
| EP809B | Black |
| EP809BZ | Bronze |
| EP809N | Nickel |



End Feed Kit

Kit includes live end feed and canopy to mount on outlet box. 4 1/2" x 4 1/2" x 1/4" thick

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP810W | White |
| EP810B | Black |
| EP810BZ | Bronze |
| EP810N | Nickel |




Dead End

Dead end cap for single and double circuit track

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP812W | White |
| EP812B | Black |
| EP812BZ | Bronze |
| EP812N | Nickel |


Single Circuit



T-Bar Ceiling Feed

Live feed with outlet box for use with T-bar ceilings

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP817W | White |
| EP817B | Black |
| EP817BZ | Bronze |
| EP817N | Nickel |



Dead Mini Connector

Dead Mini Connector to join two track sections without passing the power


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP825W | White |
| EP825B | Black |
| EP825BZ | Bronze |
| EP825N | Nickel |



T-Bar Ceiling Feed

In-line T-bar ceiling feed


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP827W | White |
| EP827B | Black |



Cord and Plug Connector

Cord and Plug Connector for single circuit track. 10 Amp MAX or 1200W. 12 ft. long


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP850W | White |
| EP850B | Black |
| EP850BZ | Bronze |
| EP850N | Nickel |



Conduit Connector

To start a surface run


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP880W | White |
| EP880B | Black |
| EP880BZ | Bronze |
| EP880N | Nickel |



Conduit Continuation Kit

Kit includes: (1) Left and (1) Right feed, to continue around obstructions with 1/2" surface conduit


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP979W | White |
| EP979B | Black |



Live Feed with Current Limiter

Current Limiter for single circuit track. 1A to 12A available

| CAT NO. | SPECIFICATIONS |
|-------------|------------------|
| EP840W-1A | White \ 1 Amp |
| EP840W-2A | White \ 2.5 Amp |
| EP840W-5A | White \ 5 Amp |
| EP840W-7A | White \ 7.5 Amp |
| EP840W-10A | White \ 10 Amp |
| EP840W-12A | White \ 12 Amp |
| EP840B-1A | Black \ 1 Amp |
| EP840B-2A | Black \ 2.5 Amp |
| EP840B-5A | Black \ 5 Amp |
| EP840B-7A | Black \ 7.5 Amp |
| EP840B-10A | Black \ 10 Amp |
| EP840B-12A | Black \ 12 Amp |
| EP840BZ-1A | Bronze \ 1 Amp |
| EP840BZ-2A | Bronze \ 2.5 Amp |
| EP840BZ-5A | Bronze \ 5 Amp |
| EP840BZ-7A | Bronze \ 7.5 Amp |
| EP840BZ-10A | Bronze \ 10 Amp |
| EP840BZ-12A | Bronze \ 12 Amp |




In-Line Feed Connector with Current Limiter

Current Limiter for single circuit track. 1A to 12A available

| CAT NO. | SPECIFICATIONS |
|------------|-----------------|
| EP841W-1A | White \ 1 Amp |
| EP841W-2A | White \ 2.5 Amp |
| EP841W-5A | White \ 5 Amp |
| EP841W-7A | White \ 7.5 Amp |
| EP841W-10A | White \ 10 Amp |
| EP841W-12A | White \ 12 Amp |
| EP841B-1A | Black \ 1 Amp |
| EP841B-2A | Black \ 2.5 Amp |
| EP841B-5A | Black \ 5 Amp |
| EP841B-7A | Black \ 7.5 Amp |
| EP841B-10A | Black \ 10 Amp |
| EP841B-12A | Black \ 12 Amp |

Two Circuit



Two Circuit Track

Track supplied with dead end and mounting hardware


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC002W | White / 2' |
| EC004W | White / 4' |
| EC006W | White / 6' |
| EC008W | White / 8' |
| EC012W | White / 12' |
| EC002B | Black / 2' |
| EC004B | Black / 4' |
| EC006B | Black / 6' |
| EC008B | Black / 8' |
| EC012B | Black / 12' |



Live End Connector

Two circuit live end connector to start a run


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC801W | White |
| EC801B | Black |



Flexible Connector

Flexible connector to join two track sections at an angle up to 90°


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC802W | White |
| EC802B | Black |



Straight Connector

Power feedable connector to join two track sections


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC803W | White |
| EC803B | Black |



L Connector

Power feedable connector to join two track sections at a 90° angle


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC804W | White |
| EC804B | Black |



T Connector

Power feedable connector to join three track sections

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC805W | White |
| EC805B | Black |



X Connector

Power feedable connector to join four track sections

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC806W | White |
| EC806B | Black |



Mini Connector

Mini Connector to join two track sections. Cannot be used as a feed point


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC808W | White |
| EC808B | Black |



Floating Canopy

Can be used anywhere along length of track to supply power. Includes end cap

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC809W | White |
| EC809B | Black |



Dead End

Dead end cap for single and double circuit track


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP812W | White |
| EP812B | Black |



T-Bar Ceiling Feed

Live feed with outlet box for use with T-bar ceilings

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC817W | White |
| EC817B | Black |



Conduit Connector

To start a surface run

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EC880W | White |
| EC880B | Black |

Two Circuit



**Two Circuit Live-End Feed Connector
with Current Limiter**

1A to 12A available. Separate circuit breaker for each circuit.
Custom current rating available upon request

| CAT NO. | SPECIFICATIONS | CIRCUIT 1 | | CIRCUIT 2 | |
|---------|----------------|-----------|----------|-----------|----------|
| EC840W | White | 1A | 1 Amp | 1A | 1 Amp |
| EC840B | Black | 2A | 2.5 Amp | 2A | 2.5 Amp |
| | | 5A | 5 Amp | 5A | 5 Amp |
| | | 7A | 7.5 Amp | 7A | 7.5 Amp |
| | | 10A | 10 Amp | 10A | 10 Amp |
| | | 12A | 12.5 Amp | 12A | 12.5 Amp |



**Two Circuit In-Line Feed Connector
with Current Limiter**

1A to 12A available. Separate circuit breaker for each circuit.
Custom current rating available upon request

| CAT NO. | SPECIFICATIONS | CIRCUIT 1 | | CIRCUIT 2 | |
|---------|----------------|-----------|----------|-----------|----------|
| EC841W | White | 1A | 1 Amp | 1A | 1 Amp |
| EC841B | Black | 2A | 2.5 Amp | 2A | 2.5 Amp |
| | | 5A | 5 Amp | 5A | 5 Amp |
| | | 7A | 7.5 Amp | 7A | 7.5 Amp |
| | | 10A | 10 Amp | 10A | 10 Amp |
| | | 12A | 12.5 Amp | 12A | 12.5 Amp |

General



Track Adapter Trim

For use with standard 6" recessed housings. Allow track lamp holders to be used with recessed installations. Up to 150W Max. 7 1/2" O.D.


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP577W | White |
| EP577B | Black |



Outlet Box Cover

Outlet box cover. Screws not included. 5" x 5" x 1/8" x 1 1/4" Sq

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP800W | White |
| EP800B | Black |
| EP800BZ | Bronze |



Monopoint Canopy

Allows any lamp holder (300W MAX.) to be converted to canopy installation. For Line Voltage fixtures

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP811W | White |
| EP811B | Black |
| EP811BZ | Bronze |
| EP811N | Nickel |



Sign Hanger

Sign Hanger with hook for single and double circuit track. Holds up to 25 lbs

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP813W | White |
| EP813B | Black |
| EP813BZ | Bronze |
| EP813N | Nickel |



Outlet Adapter

Outlet Adapter for single circuit and two circuit track

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP814W | White |
| EP814B | Black |
| EP814BZ | Bronze |
| EP814N | Nickel |



Pendant Adapter

For single circuit and two circuit track with strain relief connector for cord or chain hung fixtures. Holds up to 35 lbs

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP815W | White |
| EP815B | Black |
| EP815BZ | Bronze |
| EP815N | Nickel |



Round Monopoint Canopy

For Line Voltage fixtures. 4 5/8" O.D.

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP819W | White |
| EP819B | Black |
| EP819BZ | Bronze |



Straight Channel

Provides support for straight connection points in suspended track system. Track sits inside the channel. 16 1/4" long. Support rails for tracks

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP844W | White |
| EP844B | Black |



L Channel

Support corner connection points in suspended track system. Track sits inside the channel. 16 1/4" long in each side. Support rails for tracks

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP845W | White |
| EP845B | Black |



Dimmer Switch

Dimmer with ON/OFF switch. For Line Voltage fixtures. 150W MAX. For use with extension wands. Halogen lamps only

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP901W | White |
| EP901B | Black |



Clamp Cord and Plug

Clamp with 6 ft. cord and plug with female track connector for attaching a Line Voltage fixture

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP903W | White |
| EP903B | Black |



48" Steel Stem

For additional pendant length. Includes coupling. Use with EP918, EP924, EP936, and EP948

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP904W | White |
| EP904B | Black |

General



T-Bar Attachment Clip

Allows track to be attached to inverted T-Bar ceiling. Order as follow: (2) clips for 2' or 4' track, (3) clips for 6' track, (4) clips for 8' or 12' track

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP989B | Black |



Slope Ceiling Fixture Adapter

Allows use of extension wands on slope ceiling. 0°- 90°

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP906W | White |
| EP906B | Black |



Track Pendant Kit

Track pendant kit with 60" stainless steel cable. 1/16" stranded

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP960W | White |
| EP960B | Black |



Clamp Cord and Track Adapter

Connects to Line Voltage track. Includes female track connector for attaching a Line Voltage fixture

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP907W | White |
| EP907B | Black |



Pendant Assembly

Suspends track from ceiling. Order as follow: (2) kits for 2' or 4' track, (3) kits for 6' track, (4) kits for 8' track, (5) kits for 12', (1) EP807 per feed


| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP918W | White \ 18" |
| EP924W | White \ 24" |
| EP936W | White \ 36" |
| EP948W | White \ 48" |
| EP918B | Black \ 18" |
| EP924B | Black \ 24" |
| EP936B | Black \ 36" |
| EP948B | Black \ 48" |



Sloped Ceiling Pendant Adapter

Sloped Ceiling Pendant adapter for use with EP918, EP924, EP936, and EP948

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP905W | White |
| EP905B | Black |



Wire Cover

Wire cover for power feed through with pendant assembly. One per run. For use with EP918 to EP948

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP807W | White |
| EP807B | Black |
| EP807BZ | Bronze |
| EP807N | Nickel |



Extension Wand

Line voltage extension wands. Drops head from track

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP881W | 6" |
| EP882W | 12" |
| EP818W | 18" |
| EP824W | 24" |
| EP836W | 36" |
| EP848W | 48" |
| EP881B | 6" |
| EP882B | 12" |
| EP818B | 18" |
| EP824B | 24" |
| EP836B | 36" |
| EP848B | 48" |