

Pex™ 4" Square Deep Reflector

Pex™ Precision die-cast trims with twist-&-lock system for easy Koto™ Module installation



Features

- 4" Square Deep Reflector.
- Convenient twist-lock design for easy installation.
- Lamp: Koto™ LED Module.
- Wet location rated.



Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-lock design allows for easy mounting onto the Koto™ LED Module.

Compatible Housing: Compatible with 4" IC and non-IC housings.

Lamp: Koto™ LED Module.



Dimensions:

Options



All White



All Black



All Bronze



Black with White Ring



Chrome with White Ring



Haze with White Ring

Product Number

| Item | Finish |
|-----------|-----------|
| ELK4218BB | All Black |

Product Number Builder Example: ELK4218W

| | |
|---|--------|
| Pex™ 4" Square Deep Reflector ELK4218 | Finish |
|---|--------|


- W** All White
- BB** All Black
- BZ** All Bronze
- B** Black with White Ring
- C** Chrome with White Ring
- H** Haze with White Ring

Compatible Products



For use with 4" Koto™ Twist-&-Lock Trims

Koto™ LED Module




Koto™ LED Module
ELK07 - ELK09

| PRODUCT NUMBER BUILDER | | | | |
|------------------------|--------|--------------------------------|------------|---------------------|
| Koto™ LED Module | Lumens | Color Temperature | Beam Angle | |
| ELK | | | | |
| 07 | 750 lm | 27 2700K | (blank) | 38° lens (Standard) |
| 09 | 950 lm | 30 3000K | -S | 18° lens |
| | | 35 3500K | -N | 25° lens |
| | | 40 4000K | -W | 60° lens |
| | | SD Sunset Dimming (ELK09 Only) | | |

| ACCESSORIES | |
|---|-------------------------|
| | Lens |
| | Reflectors |
| EP731C | 18° Lens |
| EP732C | 25° Lens |
| EP733C | 38° Lens |
| EP734C | 60° Lens |
| <small>*EP732C, EP733C, EP734C Included</small> | |
| | Secondary Optics |
| L45 | Hex Louver |
| L46 | Linear Louver |
| L47 | Spread Louver |

4" Koto™ Dedicated LED ICA Housings



4" ICA Maximum Adjustability Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------|-----------------------|
| EL485ICA | Maximum Adjustability |




4" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|--------------|--|
| EL490ICA | |
| EL490ICA-EM5 | Emergency Battery Back-up (90 minutes) |



4" ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|-----------|----------------|
| EL490RICA | |




2-Hour Fire Rated 4" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------|-----------------------------|
| EL48FICA | 7 1/2" Height - Sound Rated |

Compatible Products

For use with 4" Koto™ Twist-&-Lock Trims

Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

| PRODUCT NUMBER BUILDER | | | |
|------------------------|----------------|---------------------------------------|------------------------------------|
| Koto™ LED Light Engine | Lumens | Color Temperature | Beam Angle |
| ELK | | | |
| 19 | 750 - 850 lm | 27D 2700K | (blank) 38° lens (Standard) |
| 21 | 1100 - 1500 lm | 30D 3000K | -S 18° lens |
| | | 35D 3500K | -N 25° lens |
| | | 40D 4000K | -W 60° lens |
| | | SD Sunset Dimming (ELK19 Only) | |

ACCESSORIES



Lens

- EP731C** 18° Lens
- EP732C** 25° Lens
- EP733C** 38° Lens
- EP734C** 60° Lens

*EP732C, EP733C, EP734C Included



Reflectors


- EP735C** 15°
- EP736C** 25°
- EP737C** 38°
- EP738C** 60°



Secondary Optics


- L45** Hex Louver
- L46** Linear Louver
- L47** Spread Louver

4" Koto™ Architectural Recessed Housings



4" High Lumen Maximum Adjustability ICA Housing
1500 lm (18.9W) w/ELK21 Series Module
Not for use with ELK19 Series Module
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|----------------------------|
| E4LK79ICAD | 120/277V - 0-10V/Triac/ELV |



4" Shallow Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|----------------------------|
| E4LK98ICA | 120V - Triac/ELV |
| E4LK99ICAD | 120/277V - 0-10V/Triac/ELV |



4" Standard ICA Housing
750 lm (11.8W) w/ELK19 Series Module
950 lm (11.8W) w/ELK21 Series Module
New Construction

| CAT NO. | SPECIFICATIONS |
|----------------|----------------------------|
| E4LK87ICA | 120V - Triac/ELV |
| E4LK87ICA-EM1 | Emergency Battery Back-Up |
| E4LK88ICAD | 120/277V - 0-10V/Triac/ELV |
| E4LK88ICAD-EM1 | Emergency Battery Back-Up |



4" Standard ICA Housing
750 lm (11.8W) w/ELK19 Series Module
950 lm (11.8W) w/ELK21 Series Module
Remodel

| CAT NO. | SPECIFICATIONS |
|-------------|----------------------------|
| E4LK87RICA | 120V - Triac/ELV |
| E4LK88RICAD | 120/277V - 0-10V/Triac/ELV |



2-Hour Fire Rated 4" ICA Housing
750 lm (11.8W) w/ELK19 Series Module
950 lm (11.8W) w/ELK21 Series Module
New Construction

| CAT NO. | SPECIFICATIONS |
|-------------|----------------------------|
| ELK93FICA | 120V - Triac/ELV |
| ELK94TFICAD | 120/277V - 0-10V/Triac/ELV |