

Poplar™ LED Module




Features

- Smooth lens provides even lighting illumination
- Works in 4" and 6" housing with twist-on trims
- Excellent color rendering 93+ CRI.
- UL listed for wet location
- Sunset option dims from 3000K to 1800K
- Title 24 JA8 2016-E Registered
- Life span of 50,000 hours L70

Specifications

Wattage	13.7W
Lumens	1100 lm
Voltage	120/277V
Color Temp.	3000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	93+
Wet Location	Listed

Dimensions



Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allow for efficient cooling.

Installation: Twist-On design for toolless trim installation, for use with Poplar™ trims only. Can be use in 4" and 6" housings with quick connect base. Also compatible with E26, GU10, or GU24 base housings with PSA30, PSA31, or PSA35 socket adapters (sold separately). Available for use in IC and Non-IC housings.

Electrical: Module connects to 120/277V power supply. High efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

LED Technology: Extremely accurate Color Rendering Index of 93+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixilation.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the Dimmer Compatibility List. Industry leading dimming that dims smoothly with no hot spots or flickering.

Listings: UL Listed for Wet Location. RoHS Compliant. ENERGY STAR® Certified. California Title 24 JA8-2016-E.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Product Number

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming
ELP1130	LED	1100 lm	3000K	13.7W	120/277V	Triac/ELV

Product Number Builder

Example: **ELP0827**

Poplar™ LED Module	Lumens	Color Temp.
ELP		
	08 850 lm	27 2700K
	11 1100 lm	30 3000K
		35 3500K
		40 4000K
		SD Sunset

Compatible Products



For use with Poplar™ LED Module

4" Poplar™ Dedicated LED ICA Housings



4" Recessed IC Airtight Housing
New Construction

CAT NO.	SPECIFICATIONS
EL490ICA	14W, 120V
EL490ICA-EM5	8W, Emergency Backup



4" Recessed IC Airtight Housing
Remodel

CAT NO.	SPECIFICATIONS
EL490RICA	14W, 120V

4" Flexa™ Twist-On Trims



Round Reflector

ELL4621

Finishes:
(WW, BB, CC, BZBZ, CPCP,
CW, CN, HW, BW)



Round Baffle

ELL4623

Finishes:
(WW, BB, BZBZ, BW)




Square Reflector

ELL4641

Finishes:
(WW, BB, BZBZ, BW, CW, HW)

**Not for Remodel Housing*



Square Baffle

ELL4643

Finishes:
(WW, BB, BZBZ, BW)

**Not for Remodel Housing*

4" Unique™ Twist-On Trims



Round Reflector

ELL4810

Finishes:
(W, B, BZ)



Lensed Steam Room

ELL4812

Finishes:
(W, BZ)



Round Baffle

ELL4813

Finishes:
(W, BZ)



Round Wall Wash

ELL4815

Finishes:
(W, B, BZ)



Round Deep Reflector

ELL4817


Finishes:
(W, BZ)



Round Deep Baffle

ELL4819

Finishes:
(W)




Square Reflector

ELL4814

Finishes:
(W, B, BZ)

**Not for Remodel Housing*



Square Baffle

ELL4816

Finishes:
(W, BZ)

**Not for Remodel Housing*

*Finishes: **W** - All White, **BB** - All Black, **CC** - All Chrome, **BZBZ** - All Bronze, **B** - All Black, **CPCP** - All Copper, **CW** - Chrome Reflector w/White Ring, **CN** - Chrome Reflector w/Nickel Ring, **HW** - Haze Reflector w/White Ring, **BW** - Black Reflector w/White Ring



Trimless Reflector

ELL430

Finishes:
(W, B, BZ)



Trimless Baffle

ELL434

Finishes:
(W, B, BZ)



4" Maximum Adjustability
IC Airtight Housing
New Construction


CAT NO.	SPECIFICATIONS
EL485ICA	120V / Triac/ELV dimming

Compatible Products




For use with Poplar™ LED Module

6" Poplar™ Dedicated LED ICA Housings



6" Recessed IC Airtight Housing
New Construction




6" Recessed IC Airtight Housing
Shallow New Construction



6" Recessed IC Airtight Housing
Remodel

CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS
EL770ICA	24W, 120V	EL760ICA	Shallow	EL770RICA	24W, 120/277V
		EL760ICA-EM5	8W, Emergency Backup	EL760RICA	Shallow, 120V

6" Twist-On Trims




Flexa™ Round Reflector

ELL610
Finishes:
(WW, BB, CC, BZBZ, CPCP,
CW, CN, HW, BW)




Unique™ Smooth Reflector

ELL6810
Finishes:
(W, B, BZ)



Unique™ Lensed Steam Room

ELL6812
Finishes:
(W, BZ)



Unique™ Baffle

ELL6813
Finishes:
(W, BZ)



Unique™ Wall Wash


ELL6815
Finishes:
(W, B, BZ)

Poplar™ Accessories



E26 Medium Base
to LED Quick Connect
Socket Adapter

CAT NO.	SPECIFICATIONS
PSA30	For Poplar Module




GU10
to LED Quick Connect
Socket Adapter

CAT NO.	SPECIFICATIONS
PSA31	For Poplar Module



GU24
to LED Quick Connect
Socket Adapter

CAT NO.	SPECIFICATIONS
PSA35	For Poplar Module



Hard Wire Adapter to male
Quick Connect Terminal
Socket Adapter

CAT NO.	SPECIFICATIONS
PSA38	For Poplar Module


Photometric Report

Poplar™ LED Module (850 lm/11.8W)

Multiplier: 3000K (x1.04), 3500K (x1.08), 4000K (x1.12)

PHOTOMETRIC REPORT

Product #: ELL0827
 Luminaire Lumens: 865
 Luminaire Efficacy: LPW: 80 lm/W



ILLUMINANCE AT A DISTANCE

	Center Beam Footcandles	Beam Width (Vertical Spread: 91.6°)	Beam Width (Horizontal Spread: 91.5°)
1.7'	156 fc	3.5'	3.5'
3.3'	41.3 fc	6.8'	6.8'
5.0'	18.0 fc	10.3'	10.3'
6.7'	10.0 fc	13.8'	13.8'
8.3'	6.53 fc	17.1'	17.0'
10.0'	4.50 fc	20.6'	20.5'

ZONAL LUMEN SUMMARY


Zone	Lumens	%Luminaire
0-30	340.3	35.2%
0-40	539.3	55.9%
0-60	848.1	87.9%
60-90	117.0	12.1%
70-100	39.2	4.1%
90-120	0.1	0%
0-90	965.2	100%
90-180	0.2	0%
0-180	965.3	100%

Poplar™ LED Module (1100 lm/13.7W)

Multiplier: 3000K (x1.04), 3500K (x1.08), 4000K (x1.12)

PHOTOMETRIC REPORT

Product #: ELL1127
 Luminaire Lumens: 1139
 Luminaire Efficacy: LPW: 80 lm/W



ILLUMINANCE AT A DISTANCE

	Center Beam Footcandles	Beam Width (Vertical Spread: 92.0°)	Beam Width (Horizontal Spread: 92.1°)
1.7'	182 fc	3.5'	3.5'
3.3'	48.4 fc	6.8'	6.8'
5.0'	21.1 fc	10.3'	10.4'
6.7'	11.7 fc	13.9'	13.9'
8.3'	7.65 fc	17.2'	17.2'
10.0'	5.27 fc	20.7'	20.7'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30	402.0	35.3%
0-40	639.3	56.1%
0-60	1003.4	88.1%
60-90	135.4	11.9%
70-100	45.8	4%
90-120	0.0	0%
0-90	1138.7	100%
90-180	0.2	0%
0-180	1138.9	100%



Dimmer Compatibility Chart for The Standard Poplar™ System

ELCO Lighting

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Leviton	SureSlide® Electro-Mechanical Incandescent Slide Dimmer, 600W, 120 VAC 60Hz, Single-Pole	6631	8% - 100%
	SureSlide® 600W, 120 VAC 60Hz, SureSlide Preset Electro-Mechanical Incandescent Slide Dimmer	6633	9% - 100%
	Trimatron Deluxe 3-Way Electro-Mechanical Incandescent Rotary Dimmer with Push ON/OFF	6683-IW	9% - 100%
	IllumaTech Preset Electro-Mechanical, 600W, 120VAC 60Hz, Single-Pole & 3-Way Incandescent Slide Dimmer, LED Locator	IPI06-1LZ	8% - 100%
Lutron	Ariadni® 600W 3-Way Incandescent/Halogen Dimmer	AY-603P	8% - 100%
	Ariadni® C·L Single Pole/3-Way Dimmer. 150W Max for LED/CFL or 600W Incandescent/Halogen	AYCL-153P	5% - 100%
	Ariadni® 600W Single Pole, Magnetic Low Voltage Dimmer	AYLV-600P	7% - 100%
	Skylark Contour® Single Pole/3-Way Incandescent/Halogen or Magnetic Low Voltage, Preset Dimmer	CT-103P	6% - 100%
	Skylark Contour® C·L, Single Pole/3-Way Dimmer. 150W Max LED/CFL or 600W Incandescent/Halogen	CTCL-153P	5% - 100%
	Diva® Series Single Pole Dimmer	DV-600P	10% - 100%
	Diva® (gloss) 3-Way, Electronic Low Voltage Dimmer	DVELV-303P	5% - 100%
	Maestro® C·L Single Pole/3-Way/Multi-Location Dimmer. 150W Max for LED/CFL, or 600W Incandescent/Halogen	MACL-153M	3% - 100%
	Maestro® (Gloss) Single Pole/Multi-Location, Electronic Low Voltage Dimmer	MAELV-600	6% - 100%
	Skylark® Series 600W Single Pole	S-600P	10% - 100%
	Skylark® C·L Single Pole/3-Way Dimmer. 150W Max for LED/CFL or 600W Incandescent/Halogen	SCL-153P	5% - 100%
	Skylark® 300W, Single Pole, Electronic Low Voltage, Preset Dimmer	SELV-300P	4% - 100%

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.