

Universal Dimmable LED Driver (Small)




Features

- Small universal dimmable LED drivers
- For indoor and outdoor use
- Suitable for damp locations
- Triac/ELV/MLV dimmable
- 120/277V
- ETL listed
- Class II, short circuit and overload protection

Specifications

| | |
|-----------------|------------------------------|
| Wattage | 24W - 60W |
| Voltage | 12V DC (2A) or 24V DC (2.5A) |
| Dimmable | Triac/ELV/MLV |

Dimensions



Product Numbers

| Item | Watts | Voltage | Dimming |
|--------------------|-------|---------------|---------------|
| DRVU12V24WD | 24W | 12V DC (2A) | Triac/ELV/MLV |
| DRVU12V60WD | 60W | 12V DC (5A) | Triac/ELV/MLV |
| DRVU24V24WD | 24W | 24V DC (1A) | Triac/ELV/MLV |
| DRVU24V60WD | 60W | 24V DC (2.5A) | Triac/ELV/MLV |



ELCO Lighting

Dimmer Compatibility Chart

Universal Dimmable LED Driver (Small)

For DRVU12V24WD, DRVU12V60WD, DRVU24V24WD, and DRVU24V60WD

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

| Manufacturer | Product | Part Number | Dimmed Light Output Range |
|--------------|--|-------------|---------------------------|
| Leviton | Toggle, 120V AC, 60Hz, 300W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way | TSL06-1LW | 10% - 100% |
| Legrand | 120V AC, 60Hz, 450/700W Incandescent, LED/CFL, Single Pole, 3-Way | RHCL-453P | 10% - 100% |
| Lutron | Toggle, 120V AC, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way | TGCL-153P | 10% - 100% |
| | Skylark, 120V AC, 150W CFL/LED, 600W Incandescent, Single Pole, 3-Way | SCL-153P | 10% - 100% |
| | Caseta, 120V AC, 150W CFL/LED, 600W Incandescent, Single Pole, Multi Location | PD-6WCL | 10% - 100% |
| | Diva, 120V AC, 60Hz, 600W Magnetic Low Voltage, Single Pole | DV-600P | 10% - 100% |
| | Diva, 120V AC, 60Hz, 600W Magnetic Low Voltage, Single Pole, Commercial/Residential Application | DVLV-600P | 10% - 100% |
| | Diva, 120V AC, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Commercial/Residential, Indoor Application | DVCL-153P | 10% - 100% |
| | Skylark, 120V AC, 60Hz, 600W Incandescent/Halogen, Single Pole, Commercial/Residential Application | S-600P | 10% - 100% |
| | Skylark, 120V, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way, | LG-603P | 10% - 100% |

***NOTE: Refer to dimmer manufacturer’s documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com