

| Project name: | |
|---------------|--|
| Fixture type: | |
| Date: | |

Zinnia™ LED Undercabinet Lights



Features

- Dimmable LED Undercabinet Light, polycarbonate diffuser with linear prisms.
- Suitable for row mounting.
- LED Driver: 120V AC, Triac Dimming, High Power Short Circuit/Overload Protection.
- Lamp: LED Array Module with LM-80 Certified LED chips.
- Knockout on the back and ends for easy access to wiring compartment.


Specifications

| Wattage | 9W | | |
|----------------------|-----------|--|--|
| Lumens | 800 lm | | |
| Voltage | 120V | | |
| Color Temp. | 3000K | | |
| Dimmable | Triac/ELV | | |
| Lamp Type | LED | | |
| CRI | 90 | | |
| Damp Location Listed | | | |

Options



Dimensions



Product Number

| Item | Description | Lamp type | Lumens | сст | Watts | Voltage | Dimming | Finish |
|--------|-------------|--------------|--------|-------|-------|---------|-----------|--------------|
| EUM42W | 21″ | LED | 800 lm | 3000K | 9W | 120V | Triac/ELV | All White |

Product Number Builder Example: EUM41W

ELCO LED Undercabinet Lights

Length

Finish

Length

Finish

12 1/4"

42 21"

42 21"

BZ All Bronze

43 1/4"

44 33 1/4"

45 42 1/4"



Dimmer Compatibility Chart Undercabinet

EUM 41/42/43/44/45

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

| Manufacturer | Product | Part Number | Dimmed Light Output Range |
|--------------|---|-------------|---------------------------|
| 120V Only | | | |
| Leviton | Decora IllumaTech Single Pole/3-Way Preset ON/OFF Dimmer | IPL06-10Z | 10% - 100% |
| | Decora SureSlide® Single Pole/3-Way with Preset ON/OFF Switch | 6674 | 5% - 90% |
| Lutron | DIVA® Series 150W Single Pole/3-Way Dimmer | DVCL-153P | 5% - 86% |
| | Skylark® 150W Single Pole/3-Way Dimmer | SCL-153P | 10% - 100% |
| | Maestro C•L Single Pole/3-Way/Multi-Location Dimmer | MACL-153M | 7% - 100% |

^{*}NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.