

# 6" Remodel Frame with Driver




## Features

- Optional 90 minutes, 120/277 VAC, 60Hz Emergency Backup.
- USA designed and assembled.
- LED Light Engine sold separately (see Compatible Trims).
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

## Specifications

<b>Lumens</b>	850 lm - 6000 lm
<b>Voltage</b>	120/277V or 120V
<b>Dimmable</b>	Triac/ELV/0-10V, Sunset, Lutron
<b>Power Factor</b>	≥0.9
<b>Damp Location</b>	Listed

## Dimensions



## Technical Details

### Construction:

Constructed from 16 gauge galvanized steel for commercial building applications.

### Installation:

Remodel clips hold housing sturdily into place.

**Junction Box:** Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and four pry-out knockout slots for easy romex installation.

### Electrical:

- Driver is rated for 120V and 277V input (120/277V).
- High Efficiency driver with a power factor > 0.9.
- Can be specified with Lutron drivers for specific applications.

### Dimmability:

- 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver.
- 0-10V dimming down to 51% with a compatible dimmer.
- Flicker-Free Dimming.
- Can be specified with Lutron drivers for 0.1% and 1% dimming.
- For a full list of dimmers refer to the Dimmer Compatibility List.

**Listings:** cULus Listed for Damp Location. cULus Listed for Wet Location with select trims. cULus Listed for Direct Contact with Insulation and Combustible Material for units up to 2000 lm. cULus Listed for Feed Through.

**Warranty:** ELCO Products are built to last. 5-year Limited warranty.

## Product Numbers

Item	Lumens	Voltage	Dimming
<b>E6LRU08D2</b>	850 lm	120/277V	Triac/ELV/0-10V
<b>E6LRU08S</b>	850 lm	120/277V	Sunset
<b>E6LRU08L2</b>	850 lm	120V	Lutron
<b>E6LRU12D2</b>	1250 lm	120/277V	Triac/ELV/0-10V
<b>E6LRU12S</b>	1250 lm	120/277V	Sunset
<b>E6LRU12L2</b>	1250 lm	120V	Lutron
<b>E6LRU16D2</b>	1600 lm	120/277V	Triac/ELV/0-10V
<b>E6LRU16S</b>	1600 lm	120/277V	Sunset
<b>E6LRU16L2</b>	1600 lm	120V	Lutron
<b>E6LRU20D2</b>	2000 lm	120/277V	Triac/ELV/0-10V
<b>E6LRU20S</b>	2000 lm	120/277V	Sunset
<b>E6LRU20L2</b>	2000 lm	120V	Lutron
<b>E6LRU30D2</b>	3000 lm	120/277V	Triac/ELV/0-10V
<b>E6LRU30S</b>	3000 lm	120/277V	Sunset
<b>E6LRU30L2</b>	3000 lm	120V	Lutron
<b>E6LRU40D2</b>	4000 lm	120/277V	Triac/ELV/0-10V
<b>E6LRU40L2</b>	4000 lm	120V	Lutron
<b>E6LRU60D2</b>	6000 lm	120/277V	Triac/ELV/0-10V
<b>E6LRU60L2</b>	6000 lm	120V	Lutron

Product Number Builder

Example: E6LRU08D2


ELCO Laurel 6" Remodel Frame	Voltage	Lumens	Dimming	Generation
E6LR	U 120/277V	08 850 lm 12 1250 lm 16 1600 lm 20 2000 lm 30 3000 lm 40 4000 lm 60 6000 lm	D Triac/ELV/0-10V S Sunset L Lutron	Gen 1 2 Gen 2
Optional				
(blank) No EM				
EM1 8W Emer. Backup				
EM2 12W Emer. Backup				

# Compatible Products


For use with 6" Laurel™ Frames




## 6" Laurel™ Commercial LED Light Engines




**Reflector Trim**  
**E610L**



**Wall Wash Trim**  
**E611L**



**Drop Glass Trim**  
**E612L**



**Adjustable Trim**  
**E618L**

### PRODUCT NUMBER BUILDER

Laurel™ Trim		Lumen		Color Temperature		Finish		Generation	
<b>E610L</b>	Reflector	<b>08</b>	850 lm	<b>27</b>	2700K	<b>H</b>	All Haze	<b>(blank)</b>	Gen 1
<b>E611L</b>	Wall Wash	<b>12</b>	1250 lm	<b>30</b>	3000K	<b>W</b>	All White	<b>2</b>	Gen 2
<b>E612L</b>	Drop Glass	<b>16</b>	1600 lm	<b>35</b>	3500K	<b>B</b>	All Black		
<b>E618L</b>	Adjustable	<b>20</b>	2000lm	<b>40</b>	4000K	<b>C</b>	All Chrome		
		<b>30</b>	3000lm	<b>SD</b>	Sunset Dimming	<b>HW</b>	Haze w/White Ring		
		<b>40</b>	4000lm						
		<b>60</b>	6000lm						