

6" Alva LED Ceiling Mount Disk Light



Features

- Suitable for hard wire installation into a 4" Octagon, 3 1/2" Circle or 3 1/2" Octagon junction box.
- Suitable for installation into a 5" or 6" recessed fixtures with 2-wire connector.
- Suitable for installation into a 5" or 6" recessed fixtures with medium base socket, using PSA30 adaptor (included).
- Housing meets restricted air flow requirement (per ASTM E-283).
- CA Title 24 compliant (JA8-2016).
- UL Listed.

Specifications

Wattage	13W
Lumens	900 lm
Voltage	120V
Color Temp.	2700K - 3000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	90+
Wet Location	Listed

Options



Bronze




Nickel



White

Dimensions




Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
ELSF1127W	LED	900 lm	2700K	13W	120V	Triac/ELV	White
ELSF1130BZ	LED	900 lm	3000K	13W	120V	Triac/ELV	Bronze
ELSF1130N	LED	900 lm	3000K	13W	120V	Triac/ELV	Nickel
ELSF1130W	LED	900 lm	3000K	13W	120V	Triac/ELV	White

LED Ceiling Mount Disk Light

PHOTOMETRIC REPORT

Product #: ELSF1130
Wattage/Lumens: 13W/ 931 lm
Luminaire LPW: 72 Lm/W



CANDLE POWER SUMMARY

Degrees Vertical	0°
0	296
5	296
15	289
25	272
35	247
45	214
55	174
65	128
75	81
85	39
90	23

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Footcandles Beam Center	Beam Diameter
4'	18.5	12.9'
6'	8.23	19.4'
8'	4.63	25.8'
10'	2.96	32.3'

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30°	231.29	24.80
0-40°	380.71	40.90
0-60°	683.26	73.40
0-90°	907.43	97.40