

NEW Teak™ System 2" LED Downlights & Adjustables

2" Housings & Frames

- Listed for direct contact with insulation
- UL listed - Damp location listed
- JA8 2016-E listed
- Driver included



2" R60 IC New Construction Housing

120V (Triac/ELV)		120/277V (0-10V/Triac/ELV)	
E2LAJ08ICA	850 lm	E2LAJ08ICAD	850 lm
E2LAJ11ICA	1100 lm	E2LAJ11ICAD	1100 lm



2" IC New Construction Frame

120V (Triac/ELV)		120/277V (0-10V/Triac/ELV)	
E2L08ICA	850 lm	E2L08ICAD	850 lm
E2L11ICA	1100 lm	E2L11ICAD	1100 lm



2" IC Remodel Power Pack

120V (Triac/ELV)		120/277V (0-10V/Triac/ELV)	
E2L08RIC	850 lm	E2L08RICD	850 lm
E2L11RIC	1100 lm	E2L11RICD	1100 lm

2" Light Engines

- 850 (8.6W), 1100 lm (10.5W) (Same module) Based on frame
- Listed for direct contact with insulation, Airtight
- Standard with 38° beam. Field changeable optics for 28° (EP716C) and 60° (EP718C)
- JA8 2016-E listed
- ENERGY STAR listed
- 50,000 hours L70 life-span
- Requires compatible ELCO Housings, Frame or Power Supply

2" Round Reflector



2700K	3000K
E2L10F27W	E2L10F30W
E2L10F27B	E2L10F30B
E2L10F27BZ	E2L10F30BZ
E2L10F27C	E2L10F30C
E2L10F27H	E2L10F30H

2" Square Reflector



2700K	3000K
E2L13F27W	E2L13F30W
E2L13F27B	E2L13F30B
E2L13F27BZ	E2L13F30BZ
E2L13F27C	E2L13F30C
E2L13F27H	E2L13F30H

2" Round Baffle



2700K	3000K
E2L14F27W	E2L14F30W
E2L14F27B	E2L14F30B
E2L14F27BZ	E2L14F30BZ

2" Square Baffle



2700K	3000K
E2L15F27W	E2L15F30W
E2L15F27B	E2L15F30B
E2L15F27BZ	E2L15F30BZ

2" Round Adjustable



2700K	3000K
E2L18F27W	E2L18F30W
E2L18F27B	E2L18F30B
E2L18F27BZ	E2L18F30BZ

2" Square Adjustable



2700K	3000K
E2L19F27W	E2L19F30W
E2L19F27B	E2L19F30B
E2L19F27BZ	E2L19F30BZ

(W) White - (B) Black - (BZ) Bronze - (C) Chrome - (H) Haze

E-mail your order to: orderdesk@elcolighting.com
Tel: 800.522.2626 • Fax: 800.644.2626

ELCO Lighting
The Best Choice in Lighting