

The Oak™ System 1" Mini LED Downlights

- 6W / CRI 93+ / 12V AC
- 2700K (600 lm), 3000K (625 lm), 3500K (650 lm), 4000K (675 lm)
- 38° Standard beam angle. Optional 28° (EP713C) and 50° (EP715C)
- IC Airtight for direct contact with insulation
- Height allows for use in 2x4 construction

- Remodel requires no frame
- New construction frame available
- JA8 2016-E & ENERGY STAR listed
- 50,000 hours L70 life-span



Up to 6 fixtures can be daisy-chained to one **E1LDRV60**

1" Round Downlight

2700K	E1L02F27 (W, B, BZ, H, BB)
3000K	E1L02F30 (W, B, BZ, H, BB)
3500K	E1L02F35 (W, B, BZ, H, BB)
4000K	E1L02F40 (W, B, BZ, H, BB)



1" Round Adjustable Gimbal

2700K	E1L32F27 (W, B, BZ)
3000K	E1L32F30 (W, B, BZ)
3500K	E1L32F35 (W, B, BZ)
4000K	E1L32F40 (W, B, BZ)



1" Square Downlight

2700K	E1L12F27 (W, B, BZ, H, BB)
3000K	E1L12F30 (W, B, BZ, H, BB)
3500K	E1L12F35 (W, B, BZ, H, BB)
4000K	E1L12F40 (W, B, BZ, H, BB)



1" Square Adjustable Pull-Down

2700K	E1L22F27 (W, B, BZ)
3000K	E1L22F30 (W, B, BZ)
3500K	E1L22F35 (W, B, BZ)
4000K	E1L22F40 (W, B, BZ)



(W) All White - (B) Black/Wht Ring - (BZ) All Bronze - (H) Haze/Wht Ring - (BB) All Black

(W) All White - (B) All Black - (BZ) All Bronze

Electronic Transformer

E1LDRV60

- 60W, 12V AC output, 120V input
- To Daisy chain Oak™ System fixtures
- Electronic Low Voltage (ELV) dimmable



Oak™ Frames and Housings

Check our full selection of Frames and Housings at elcolighting.com or order **The Oak™ System** catalog at orderdesk@elcolighting.com



Requires 12V AC Transformer

Single Cutout Frames

E1LF1 For Downlights
E1LF2 For Adjustables



Requires 12V AC Transformer

Multiple Cutout Frames

E1LF1 (M2, M3, M4, M5) For Downlights
E1LF2 (M2, M3, M4, M5) For Adjustables

Consult for pricing

12V AC Transformer Included



R60 ICA Housings

E1LF1CAJ For Downlights
E1LF2ICAJ For Adjustables

E-mail your order to: orderdesk@elcolighting.com
Tel: **800.522.2626** • Fax: **800.644.2626**



ELCO Lighting
The Best Choice in Lighting