

6" Dedicated LED Housings & Inserts

6" Dedicated LED IC Housings

- Quick connect for easy installation
- Meets Title 24 requirements



2-Hour Fire Rated IC Airtight Housing

- Sound Rated
- 7 3/4" Height - 6 3/8" Opening

EL76FICA

EL76FICA-7 (277V)



IC Airtight New Construction Housing

Standard - 7" Height - 6 1/4" Opening

EL770ICA

EL770ICA-7 (277V)

Shallow - 5 1/2" Height - 6 1/4" Opening

EL760ICA

EL760ICA-7 (277V)



IC Airtight Remodel Housing

Standard - 7 1/2" Height - 6 1/2" Opening

EL770RICA

EL770RICA-7 (277V)

Shallow - 5 1/2" Height - 6 1/4" Opening

EL760RICA

HIGHLUMEN 6" LED Inserts

- Quick connect for easy installation
- Medium base adaptor included
- CRI 90+

LED Round Baffle

- 7 1/2" O.D.

EL61130W 14W, 1000 lm, 3000K

EL61140W 14W, 1100 lm, 4000K

EL61230W 20W, 1400 lm, 3000K

LED Round Reflector

- 7 1/2" O.D.

EL61727W 14W, 1000 lm, 2700K

EL61730W 14W, 1000 lm, 3000K

EL61735W 14W, 1100 lm, 3500K

EL61740W 14W, 1100 lm, 4000K

EL62727W 20W, 1400 lm, 2700K

EL62730W 20W, 1400 lm, 3000K

EL62735W 20W, 1400 lm, 3500K

EL62740W 20W, 1400 lm, 4000K

- Dimmable Triac/ELV
- Title 24 Compliant
- UL Listed

LED Round Deep Baffle

- 7 1/2" O.D.

EL62127W 14W, 1000 lm, 2700K

EL62130W 14W, 1000 lm, 3000K

LED Round Deep Reflector

- 7 1/2" O.D.

EL62527W 14W, 1000 lm, 2700K

EL62530W 14W, 1000 lm, 3000K

EL62527C 14W, 1000 lm, 2700K

EL62530C 14W, 1000 lm, 3000K

EL62535C 14W, 1100 lm, 3500K

EL62540C 14W, 1100 lm, 4000K

EL62527H 14W, 1000 lm, 2700K

EL62530H 14W, 1000 lm, 3000K

EL62535H 14W, 1100 lm, 3500K

EL62540H 14W, 1100 lm, 4000K

FINISHES: (W) All White (C) Chrome/Wht Ring (H) Haze/Wht Ring

LED Round CCT Reflector

EL625CT5W

- 12W / 120V / CRI 90+
- 880 lm-1080 lm, 2700K-5000K
- UL listed for wet location
- Dimmable Triac/ELV
- 7 1/2" O.D.



- Switch to desire CCT
- 2700K (880 lm)
 - 3000K (960 lm)
 - 3500K (1040 lm)
 - 4000K (1060 lm)
 - 5000K (1080 lm)

Subject to US tariffs. All other standards, terms and conditions apply.

Please provide your e-mail address to salesadmin@elcolighting.com. To unsubscribe e-mail: salesadmin@elcolighting.com

E-mail your order to: orderdesk@elcolighting.com

Tel: 800.522.2626 • Fax: 800.644.2626



ELCO Lighting

The Best Choice in Lighting