

Introducing our **NEW Elm™ System**


LED Gimbal Downlights



Switch to
desired CCT
2700K, 3000K,
3500K, 4000K,
5000K

120V RECESSED GIMBAL DOWNLIGHT WITH 5-CCT SWITCH

Designed to be installed without the need for a housing. • **IC Airtight** for direct contact with insulation
25° tilt range • 120V driver • 90+ CRI • ETL listed • Triac/ELV dimmable • Life span of 50,000 hours L70



4" LED Recessed Gimbal Downlight with 5-CCT Switch

- 10W, 650 lm, CRI 90+
- CCT Switch: 2700K, 3000K, 3500K, 4000K, 5000K
- 5" O.D. - 3" Gimbal Diameter

ERT413CT5W

6" LED Recessed Gimbal Downlight with 5-CCT Switch

- 15W, 900 lm, CRI 90+
- CCT Switch: 2700K, 3000K, 3500K, 4000K, 5000K
- 7 1/8" O.D. - 4 5/8" Gimbal Diameter

ERT613CT5W

Check out our full line of
Elm™ System Downlights at elcolighting.com

Elm™ System Frames & Accessories

Plaster Frames with Hanger Bars



E4LF1 4" Round


E6LF1 6" Round

Universal Frame



E246LF1 2", 4" & 6" Round

Mounting Plates



EMP4 4" Round

EMP6 6" Round

Extension Cables



ECNE10 10 inch cable

ECNE11 10 foot cable

Subject to US tariffs. All other standards, terms and conditions apply.
Please provide your e-mail address to salesadmin@elcolighting.com. To unsubscribe e-mail: salesadmin@elcolighting.com



E-mail your order to: orderdesk@elcolighting.com

Tel: 800.522.2626 • Fax: 800.644.2626

ELCO Lighting
The Best Choice in Lighting