

## 4" & 6" Ply Sylo™

# Pendant & Surface Mount



This unique **Ply Sylo™ LED Pendant & Surface Mount** gives you the options you are looking for. Engineered with energy-efficient LED technology and dimming options for your project.

### 4" & 6" Ply Sylo™ Surface Mount

- Modern Surface Mount die-cast aluminum fixture for easy maintenance and upgrades
- Fits 3 1/2" and 4" Octagon and Round Junction boxes
- Manual switch to choose desired color temperature and lumen output



Product #	Wattage	CCT	Lumens	Voltage/Dimming
<b>ESF4271L3CT5 (W, BB, HW)</b>	12.5, 16, 18W	2700K-5000K	1000, 1250, 1500 lm	120V, Triac/ELV
<b>4" ESF427110CT5 (W, BB, HW)</b>	15W	2700K-5000K	1000 lm	120V, Triac/ELV
<b>ESF475UL3CT5 (W, BB, HW)</b>	9.5, 13, 18W	2700K-5000K	850, 1000, 1500 lm	120/277V, 0-10V
<b>ESF6371L3CT5 (W, BB, HW)</b>	14, 18, 24W	2700K-5000K	1000, 1500, 2000 lm	120V, Triac/ELV
<b>6" ESF637110CT5 (W, BB, HW)</b>	15W	2700K-5000K	1000 lm	120V, Triac/ELV
<b>ESF685UL3CT5 (W, BB, HW)</b>	14, 18, 24W	2700K-5000K	1000, 1500, 2000 lm	120/277V, 0-10V

### 4" & 6" Ply Sylo™ Pendant

- Modern Pendant die-cast aluminum fixture for easy maintenance and upgrades
- 120" field cuttable cable
- Fits 3 1/2" and 4" Octagon and Round Junction boxes
- Manual switch to choose desired color temperature and lumen output



Product #	Wattage	CCT	Lumens	Voltage/Dimming
<b>EPD4271L3CT5 (W, BB, HW)</b>	12.5, 16, 18W	2700K-5000K	1000, 1250, 1500 lm	120V, Triac/ELV
<b>4" EPD427110CT5 (W, HW)</b>	15W	2700K-5000K	1000 lm	120V, Triac/ELV
<b>EPD475UL3CT5 (W, BB, HW)</b>	9.5, 13, 18W	2700K-5000K	850, 1000, 1500 lm	120/277V, 0-10V
<b>EPD6371L3CT5 (W, BB, HW)</b>	14, 18, 24W	2700K-5000K	1000, 1500, 2000 lm	120V, Triac/ELV
<b>6" EPD637110CT5 (W, BB, HW)</b>	15W	2700K-5000K	1000 lm	120V, Triac/ELV
<b>EPD685UL3CT5 (W, BB, HW)</b>	14, 18, 24W	2700K-5000K	1000, 1500, 2000 lm	120/277V, 0-10V

Available Colors: (W) All White, (BB) All Black, (HW) Haze/White Ring

Subject to US tariffs. All other standards, terms and conditions apply.  
Please provide your e-mail address to salesadmin@elcolighting.com. To unsubscribe e-mail: salesadmin@elcolighting.com



E-mail your order to: [orderdesk@elcolighting.com](mailto:orderdesk@elcolighting.com)  
Tel: 800.522.2626 • Fax: 800.644.2626

**ELCO Lighting**  
The Best Choice in Lighting