


Introducing our new **900 lm ARCHITECTURAL** **Oak™ System**

Download a FREE digital copy of our Architectural Oak™ System Catalog (ELCAT1069) at elcolighting.com



Our smallest LED recessed downlights and adjustables are engineered to squeeze into the tiniest of spaces, yet still provide enough power to light up the surroundings. Push-&-twist connector for easy installation into New Construction or Remodel applications.

1" Round & Square Downlights

- Delivers up to 1000 lumens
- Wet location rated
- IC Airtight for direct contact with insulation

Lumens: 850 - 1000 lm
Color Temp: 2700K-4000K, Sunset
CRI: 93+



New Construction Applications

- Driver included
- Driver specified for 120V or 120/277V

Oak™ R60 IC Airtight New Construction Housing



Oak™ IC New Construction Frame



Remodel Application

- Driver specified for 120V or 120/277V
- Mounting Frames available

Oak™ IC Remodel Power Pack



| 1" Oak™ Architectural Downlight | Style | Beam Angle | Color Temperature | Finish |
|---------------------------------|------------------|-------------------------|-------------------|-------------------------|
| E1AK | | | | |
| Product Number Builder | 02 Round | F 38° (Standard) | 27 2700K | W All White |
| | 12 Square | NF 28° | 30 3000K | B Black/Wht Ring |
| | | WF 50° | 35 3500K | BZ All Bronze |
| | | | 40 4000K | H Haze/Wht Ring |
| | | | SD Sunset | BB All Black |

Example: **E1AK02F40BB** [1" Oak™ Round Downlight, 38° Beam Angle, 4000K, All Black]

1" Round & Square Adjustables

- Delivers up to 900 lumens
- 30° Gimbal adjustability
- Damp location rated
- IC for direct contact with insulation

Lumens: 850 - 900 lm
Color Temp: 2700K-3000K
CRI: 93+



| 1" Oak™ Architectural Adjustables | Style | Beam Angle | Color Temperature | Finish |
|-----------------------------------|----------------------------|-------------------------|-------------------|--------------------|
| E1AK | | | | |
| Product Number Builder | 32 Round Gimbal | F 38° (Standard) | 27 2700K | W All White |
| | 22 Square Pull Down | NF 28° | 30 3000K | B All Black |
| | | WF 50° | | |
| | | | | |
| | | | | |

Example: **E1AK32F30W** [1" Oak™ Round Gimbal, 38° Beam Angle, 3000K, All White]

Subject to US tariffs. All other standards, terms and conditions apply.
Please provide your e-mail address to salesadmin@elcolighting.com. To unsubscribe e-mail: salesadmin@elcolighting.com



E-mail your order to: orderdesk@elcolighting.com
Tel: **800.522.2626** • Fax: **800.644.2626**

ELCO Lighting
The Best Choice in Lighting