

4" Adjustable Koto Sylo™

Pendant & Surface Mount



This unique **Koto Sylo™ LED Pendant & Surface Mount** gives you the options you are looking for. Modern die-cast aluminum fixtures for easy maintenance and upgrades. **Sunset** option dims from 3000K to 1800K. **Human Centric** option dims from 4000K to 2700K. Energy Star Certified. Title 24 JA8-2022 Compliant.



Low Voltage Koto Sylo™
 fixtures also available.
 Check them out at
elcolighting.com



Also available
 with **Stems**
 (12", 24", 36" & 48")

4" Adjustable Koto Sylo™ Surface Mount

- 30° MAX. tilt adjustability
- Fits 3 1/2" and 4" Octagon and Round Junction boxes
- Includes standard 38° lens, with 28° and 60° lenses.
 Optional: 15° & 18° lenses available

4" Adjustable Koto Sylo™ Pendant

- 30° MAX. tilt adjustability
- 120" field cuttable cable
 Optional: 12", 24", 36" and 40" Stems available
- Fits 3 1/2" and 4" Octagon and Round Junction boxes
- Includes standard 38° lens, with 28° and 60° lenses.
 Optional: 15° & 18° lenses available

Product Number Builder

Adjustable Koto Sylo™	Finish	Koto™ LED Module	Color Temperature	Voltage	Beam Angle
E429P Pendant	W All White	-03 350 lm (2400K, 2700K, 3000K Only)	24 2400K	D 120V, Triac/ELV	38° lens
E429F Surface Mount	B All Black	-07 750 lm	27 2700K	120/277V, 0-10V, Triac/ELV	-S 18° lens
	S All Silver	-09 950 lm	30 3000K		-N 28° lens
		-11 1150 lm	35 3500K		-W 60° lens
		-13 1350 lm	40 4000K		-T 10° lens
		-08 825 lm (CT5 Only)	SD Sunset (-09 & -11 Only)		(-03 & -07, 2700K & 3000K Only)
		-10 1000 lm (CT5 Only)	HC Human Centric (-11 Only)		
			CT5 2700K - 5000K		

Example: **E429PW-0327** [Koto Sylo™ Adjustable Pendant, All White, 350 lm, 2700K, 120V, Triac/ELV, 38° Beam Angle]

Subject to US tariffs. All other standards, terms and conditions apply.
 Please provide your e-mail address to salesadmin@elcolighting.com. To unsubscribe e-mail: salesadmin@elcolighting.com



E-mail your order to: orderdesk@elcolighting.com
 Tel: **800.522.2626** • Fax: **800.644.2626**

